

Page



Powertec Wireless Technology
ABN: 42 082 948 463
PO Box 1034, Ashmore City
Queensland, Australia, 4214
sales@powertec.com.au
1300 769 378

RG-402 Patch Cable N Female to SMA Male Low PIM 50cm

SKU
ACC-PT-00364
MPN
CA-R402-N2SA1.050
Barcode
9337692002540

Description

The RG-402 Patch Cable, model ACC-PT-00364, is a high-performance RF cable developed by Powertec, suitable for component interconnection in various applications. This 50 cm cable features an N Female to SMA Male connection and is made from Powertec's PSF-402 series, a 0.141" semi-flexible, low-loss coaxial cable with a 4.2 mm bright blue outer jacket. It supports frequencies up to 34 GHz, making it versatile for microwave and RF applications.

The PSF-402 cable is known for its hand-formability, excellent shielding, and very low passive intermodulation (PIM), with a 3rd Order PIM rating of -120 dBc. Its construction includes a tin-soaked copper braid that provides nearly 100% RF shielding, enhancing durability by preventing solder joint failures and allowing tight bends. It can endure over 500 mating cycles.

The cable operates within a frequency range of 0 to 6 GHz, with a VSWR of $\leq 1.2:1$ at 3000 MHz and $\leq 1.5:1$ at 6000 MHz, ensuring...

[Read More](#)





Powertec

Powertec is a wireless technology manufacturer and systems integrator based in Australia. Operating since 1995, Powertec has grown to become the leading wireless technology distributor in its region, and a leading Infratech systems developer. Supporting over 1500 partners the company provides procurement, design, project management, and support services across Australia, New Zealand, Pacific ...

RF Specification

Start Frequency

0 GHz

PIM, 3rd Order

-120 dBc

Stop Frequency

6 GHz

VSWR Measurement

Frequency VSWR

3000 MHz $\leq 1.2:1$

6000 MHz $\leq 1.5:1$

Physical Specification

Subtype

[Patch Cable](#)

Mating Cycles

> 500

Compliance/Certifications

,

RoHS

Length

0.5 m

Weight

63 g


RF Connectors

RF Interface Body Shape Mounting

N Female Straight Free Hanging

SMA Male Straight Free Hanging

Drawing



PSF-402

Min. Frequency

0 GHz

Impedance

50 Ω

Min. Bend Radius Static

8 mm

Min. Bend Radius Dynamic

40 mm

Max. Frequency

34 GHz

Shielding Effectiveness

> 110 dB

Colour

Blue

Cable Layers

| Layer | Diameter | Materials |
|-----------------|----------|---|
| Inner Conductor | 0.93 mm | Silver Plated Copper (SC) |
| Dielectric | 3.00 mm | PTFE / Teflon |
| Outer Conductor | 3.52 mm | Tin Soaked Copper Braid |
| Outer Jacket | 4.20 mm | Polyolefin LSZH |

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

