

L-195 Coaxial Cable N Male to SMA Male, 20m

SKU: ACC-PT-00379
 MPN: CA-P195-N1SA1.20
 Barcode: 9337692003677

Description

RF Specification

Start Frequency:	0 GHz	Stop Frequency:	6 GHz
------------------	-------	-----------------	-------

Physical Specification

Subtype:	Feeder Cable	Length:	20 m
Mating Cycles:	> 500	Weight:	650 g
Compliance/Certifications:	ISO 9001 Quality Management		
RoHS			

RF Connectors

RF Interface	Body Shape	Mounting
N Male	Straight	Free Hanging
SMA Male	Straight	Free Hanging



PTL-195

Powertec

Powertec is a wireless technology manufacturer and systems integrator based in Australia. Operating since 1995, Powertec has grown to become the leading wireless technology distributor in its region, and a leading Infratech systems developer. Supporting over 1500 partners the company provides procurement, design, project management, and support services across Australia, New Zealand, Pacific ...

Min. Frequency:	0 GHz	Max. Frequency:	6 GHz
Impedance:	50	Shielding Effectiveness:	> 90 dB
Min. Bend Radius Static:	12.7 mm	Colour:	Black
Min. Bend Radius Dynamic:	50.8 mm	Weight (g/m):	30 g

Cable Layers

Layer	Diameter	Materials
Inner Conductor	0.94 mm	Solid Copper
Dielectric	2.97 mm	Foamed Polyethylene (EPE)
Outer Conductor	2.95 mm	Aluminium Foil (Bonded)
Outer Conductor	3.53 mm	Tinned Copper Braid (TC)
Outer Jacket	4.95 mm	Polyethylene (PE)

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

