# POWERTEC | DATASHEET | UNCONTROLLED WHEN PRINTED PUBLIC | August 1, 2025 08:32

Page



Powertec Wireless Technology ABN: 42 082 948 463 PO Box 1034, Ashmore City Queensland, Australia, 4214 sales@powertec.com.au 1300 769 378

# 4.3-10 Male Four-Hole Flange Connector with Round Post

SKU ACC-PT-00418 MPN 431-4F-RP001


#### **Description**

The 4.3-10 Male Four-Hole Flange Connector with Round Post (SKU: ACC-PT-00418) by Powertec, part number 431-4F-RP001, is a high-quality RF connector designed for reliable performance in various applications. This coaxial connector features a straight body with a four-hole flange front mount, ideal for secure attachment to cables using a round post mechanism.

Constructed with a robust brass body and inner contacts, both plated in silver, it ensures excellent conductivity and durability. The PTFE/Teflon insulator offers superior electrical insulation, supporting an input impedance of 50  $\Omega$  and insulation resistance of  $\geq$  5000 m $\Omega$ . It operates efficiently across a frequency range of 0 to 3.0 GHz, handling RF operating voltage up to 500 Vrms.

This connector is designed to endure multiple mating cycles and performs optimally within a specified temperature range. It exhibits a low VSWR of  $\leq$  1.20:1, ensuring minimal signal reflection. The product...

#### Read More





**Powertec** 

Powertec is a wireless technology manufacturer and systems integrator based in Australia. Operating since 1995, Powertec has grown to become the leading wireless technology distributor in its region, and a leading Infratech systems developer. Supporting over 1500 partners the company provides procurement, design, project management, and support services across Australia, New Zealand, Pacific ...

#### **RF Connector Interface**

RF Interface Body Shape Mounting

4.3-10 Male Straight 4-Hole Flange

## **RF Specification**

Start Frequency

0 GHz

**Stop Frequency** 

3 GHz

Input Impedance

50 Ω

Insulation Resistance

 $\geq$  5000 m $\Omega$ 

RF Operating Voltage

≤ 500 Vrms

**VSWR** Measurement

Frequency VSWR

 $3000 \text{ MHz} \leq 1.2:1$ 

### **Physical Specification**

**Body Material** 

**Brass** 

**Body Plating** 

Silver

**Insulator Material** 

PTFE / Teflon

**Dimensions** 

34.8 x 25.4 x 19

Compliance/Certifications

**RoHS** 

**Conductor Attachment** 

**Round Post** 

**Contact Material** 

**Brass** 

**Contact Plating** 

Silver

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

