

Powertec Wireless Technology ABN: 42 082 948 463 PO Box 1034, Ashmore City Queensland, Australia, 4214 sales@powertec.com.au 1300 769 378

Powertec 4G-5G Wideband LPDA Antenna, 698 to 4000 MHz, 4.3-10 Female

SKU: ANT-PT-00021 MPN: LLP-6940-7.432 Barcode: 9337692005022

Description

The LLP-6940-7 mini log periodic antenna is designed for outdoor applications requiring wideband operation, medium gain, with a compact form-factor. It operates across a frequency range of 698 MHz to 4000 MHz, making it suitable for various telecommunications applications, including cellular networks, wireless broadband, and other RF communication systems. Its vertical polarisation enhances its ability to maintain signal integrity in diverse environmental conditions.

With a VSWR of less than 2.0:1 across its range, the antenna ensures efficient power transfer and minimal signal reflection. The construction features a UV-stabilised ABS plastic radome, offering resilience in harsh weather conditions, with an operational temperature range from -40 °C to 65 °C.

The antenna's 4.3-10 female connector ensures secure and weatherproof connectivity. It is lightweight at 1.1 kg and compact, facilitating easy installation on poles with diameters...

Read More





Powertec

Powertec is a wireless technology manufacturer and systems integrator based in Australia. Operating since 1995, Powertec has grown to become the leading wireless technology distributor in its region, and a leading Infratech systems developer. Supporting over 1500 partners the company provides procurement, design, project management, and support services across Australia, New Zealand, Pacific ...

RF Specification

| Start Frequency: | 698 MHz | Polarisation: | Vertical (V) |
|-------------------|----------|------------------|--------------|
| Stop Frequency: | 4000 MHz | Input Impedance: | 50 |
| Max. Input Power: | 50 W | | |

RF Connectors

| Ports | RF Interface | Body Shape | Cable Series | Length |
|-------|---------------|------------|--------------|--------|
| 1 | 4.3-10 Female | Straight | PSF-402 | 300 mm |

Frequency Test Data

| 698 MHz 960 MHz 9.5 dBi < 2:1 90° 66° 1710 MHz 2700 MHz 11 dBi < 1.5:1 75° 58° | F/B Ratio |
|---|-----------|
| 1710 MHz 2700 MHz 11 dB; 415.1 75° 50° | > 15 dB |
| 17 10 WINZ 2700 WINZ 11 UBI < 1.5.1 /5 56 | > 12 dB |
| 3300 MHz 4000 MHz 11.5 dBi < 1.8:1 54° 42° | > 15 dB |

Physical Specification

| Subtype: | Log Periodic Dipole Array | Dimensions: | 440x205x60 |
|-----------------------------|---------------------------|-------------|------------------------|
| Input Ports: | 1 | Materials: | ABS Plastic, Aluminium |
| MIMO: | 1x1 SISO | Mounting: | Pole Clamp 30 to 52 mm |
| Min. Operating Temperature: | -40 °C | Weight: | 1.1 kg |
| Max. Operating Temperature: | 65 °C | | |

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

