

Page



Powertec Wireless Technology
ABN: 42 082 948 463
PO Box 1034, Ashmore City
Queensland, Australia, 4214
sales@powertec.com.au
1300 769 378

PTL-400 Coaxial Cable 4.3-10 Male to 4.3-10 Male 5m

SKU
IBC-PT-00003
MPN
CA-P400-431431.5

Description

The PTL-400 Coaxial Cable by Powertec, part number CA-P400-431431.5, features dual 4.3-10 Male connectors over a 5m length. As part of the PTL-400 series, this cable is an L-400 class low loss coaxial cable with a 10.29 mm outer diameter, capable of supporting frequencies up to 6 GHz. Ideal for entry- to intermediate-level wireless communication systems, it is flexible, featuring a double outer conductor made of aluminium tape and tinned copper braiding, ensuring RF shielding exceeding 90 dB. The durable PE jacket extends its service life beyond 20 years, and it can handle over 500 mating cycles.

The cable operates effectively within a frequency range of 0 to 6 GHz and meets ISO 9001 Quality Management and RoHS certifications. Both ends are equipped with 4.3-10 Male connectors in a straight, free-hanging mounting style. Weighing 550 g, it offers reliable performance in various environments. Powertec, established in 1995, is a leading...

[Read More](#)





Powertec

Powertec is a wireless technology manufacturer and systems integrator based in Australia. Operating since 1995, Powertec has grown to become the leading wireless technology distributor in its region, and a leading Infratech systems developer. Supporting over 1500 partners the company provides procurement, design, project management, and support services across Australia, New Zealand, Pacific ...

RF Specification

Start Frequency

0 GHz

Stop Frequency

6 GHz

Physical Specification

Subtype

[Feeder Cable](#)

Mating Cycles

> 500

Compliance/Certifications

[ISO 9001 Quality Management](#)

,

[RoHS](#)

Length

5 m

Weight

550 g

RF Connectors

RF Interface Body Shape Mounting

[4.3-10 Male](#) [Straight](#) [Free Hanging](#)

[4.3-10 Male](#) [Straight](#) [Free Hanging](#)

PTL-400

Min. Frequency

0 GHz

Impedance

50 Ω

Min. Bend Radius Static

25.4 mm

Min. Bend Radius Dynamic

101.6 mm

Max. Frequency

6 GHz

Shielding Effectiveness

> 90 dB

Colour

Black

Weight (g/m)

100 g

Cable Layers

Layer	Diameter	Materials
Inner Conductor	2.74 mm	Copper Clad Aluminium (CCA)
Dielectric	7.24 mm	Foamed Polyethylene (EPE)
Outer Conductor	7.39 mm	Aluminium Foil (Bonded)
Outer Conductor	8.13 mm	Tinned Copper Braid (TC) , Tinned Copper Clad AlMg
Outer Jacket	10.29 mm	Polyethylene (PE)

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE

LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE
RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE
INFORMATION.

