

Page



Powertec Wireless Technology
ABN: 42 082 948 463
PO Box 1034, Ashmore City
Queensland, Australia, 4214
sales@powertec.com.au
1300 769 378

PTL-400 Coaxial Cable 4.3-10 Male to 4.3-10 Male 10m

SKU
IBC-PT-00004
MPN
CA-P400-431431.10
Barcode
9337692002182

Description

The PTL-400 Coaxial Cable (SKU: IBC-PT-00004) is a high-performance RF cable featuring 4.3-10 Male connectors on both ends. Designed by Powertec, this cable supports frequencies up to 6 GHz, making it ideal for entry to intermediate-level wireless communication systems.

The PTL-400 is a low-loss, L-400 class cable with a 10.29 mm outer diameter and features a flexible design with a double outer conductor composed of aluminium tape and tinned copper braiding. This double shielding ensures exceptional RF shielding performance exceeding 90 dB, while the durable PE jacket offers a service life of over 20 years. The cable measures 10 metres in length and weighs 1050 grams, providing robust yet flexible connectivity solutions.

Engineered for high durability, the cable withstands over 500 mating cycles, ensuring long-term reliability. It meets ISO 9001 Quality Management standards and is RoHS compliant, reflecting Powertec's commitment to...

[Read More](#)





Powertec

Powertec is a wireless technology manufacturer and systems integrator based in Australia. Operating since 1995, Powertec has grown to become the leading wireless technology distributor in its region, and a leading Infratech systems developer. Supporting over 1500 partners the company provides procurement, design, project management, and support services across Australia, New Zealand, Pacific ...

RF Specification

Start Frequency

0 GHz

Stop Frequency

6 GHz

Physical Specification

Subtype

[Feeder Cable](#)

Mating Cycles

> 500

Compliance/Certifications

[ISO 9001 Quality Management](#)

,

[RoHS](#)

Length

10 m

Weight

1050 g

RF Connectors

RF Interface Body Shape Mounting

[4.3-10 Male](#) [Straight](#) [Free Hanging](#)

[4.3-10 Male](#) [Straight](#) [Free Hanging](#)

PTL-400

Min. Frequency

0 GHz

Impedance

50 Ω

Min. Bend Radius Static

25.4 mm

Min. Bend Radius Dynamic

101.6 mm

Max. Frequency

6 GHz

Shielding Effectiveness

> 90 dB

Colour

Black

Weight (g/m)

100 g

Cable Layers

Layer	Diameter	Materials
Inner Conductor	2.74 mm	Copper Clad Aluminium (CCA)
Dielectric	7.24 mm	Foamed Polyethylene (EPE)
Outer Conductor	7.39 mm	Aluminium Foil (Bonded)
Outer Conductor	8.13 mm	Tinned Copper Braid (TC) , Tinned Copper Clad AlMg
Outer Jacket	10.29 mm	Polyethylene (PE)

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE

LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE
RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE
INFORMATION.

