

PTL-400 Coaxial Cable 4.3-10 Male to 4.3-10 Male 15m

SKU: IBC-PT-00005

MPN: CA-P400-431431.15

Barcode: 9337692002199

Description

The PTL-400 Coaxial Cable, part number CA-P400-431431.15, is a premium RF cable from Powertec, designed for high-performance wireless communication systems. This 15m cable features 4.3-10 Male connectors on both ends, offering a straight body shape and free hanging mounting style. Engineered with a 10.29 mm outer diameter, the PTL-400 is an L-400 class low loss coaxial cable that supports frequencies up to 6 GHz, making it ideal for a range of applications from entry to intermediate-level systems.

The cable's construction includes a double outer conductor of aluminium tape and tinned copper braiding, which ensures superior RF shielding exceeding 90 dB. Encased in a durable PE jacket, the PTL-400 is built to last over 20 years and withstand more than 500 mating cycles. Weighing 1550 grams, this flexible cable meets ISO 9001 Quality Management and RoHS certifications for assured quality and environmental compliance.

Powertec, an Australian...

[Read More](#)



RF Specification

Start Frequency:

 WIRELESS TECHNOLOGY

Powertec
0 GHz

Stop Frequency:

6 GHz

Powertec is a wireless technology manufacturer and systems integrator based in Australia. Operating since 1995, Powertec has grown to become the leading wireless technology distributor in its region, and a leading Infratech systems developer. Supporting over 1500 partners the company provides procurement, design, project management, and support services across Australia, New Zealand, Pacific ...

Physical Specification

| | | | |
|----------------------------|-----------------------------|---------|--------|
| Subtype: | Feeder Cable | Length: | 15 m |
| Mating Cycles: | > 500 | Weight: | 1550 g |
| Compliance/Certifications: | ISO 9001 Quality Management | | |
| RoHS | | | |

RF Connectors

| RF Interface | Body Shape | Mounting |
|--------------|------------|--------------|
| 4.3-10 Male | Straight | Free Hanging |
| 4.3-10 Male | Straight | Free Hanging |

PTL-400

| | | | |
|---------------------------|----------|--------------------------|---------|
| Min. Frequency: | 0 GHz | Max. Frequency: | 6 GHz |
| Impedance: | 50 | Shielding Effectiveness: | > 90 dB |
| Min. Bend Radius Static: | 25.4 mm | Colour: | Black |
| Min. Bend Radius Dynamic: | 101.6 mm | Weight (g/m): | 100 g |

Cable Layers

| Layer | Diameter | Materials |
|-----------------|----------|---|
| Inner Conductor | 2.74 mm | Copper Clad Aluminium (CCA) |
| Dielectric | 7.24 mm | Foamed Polyethylene (EPE) |
| Outer Conductor | 7.39 mm | Aluminium Foil (Bonded) |
| Outer Conductor | 8.13 mm | Tinned Copper Braid (TC), Tinned Copper Clad AlMg |
| Outer Jacket | 10.29 mm | Polyethylene (PE) |

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

