Powertec Wireless Technology
ABN: 42 082 948 463
PO Box 1034, Ashmore City
Queensland, Australia, 4214
sales@powertec.com.au
1300 769 378

PTL-400 Coaxial Cable 4.3-10 Male to 4.3-10 Male 20m

SKU
IBC-PT-00006
MPN
CA-P400-431431.20
Barcode
9337692002205

Description

The PTL-400 Coaxial Cable, 4.3-10 Male to 4.3-10 Male, 20m (SKU: IBC-PT-00006), by Powertec, is a top-tier solution for wireless communications systems. This PTL-400 series cable is a low-loss coaxial cable with a 10.29 mm outer diameter, capable of supporting frequencies up to 6 GHz, making it ideal for entry to intermediate-level applications.

The cable features a flexible design with a double outer conductor, combining aluminium tape and tinned copper braiding. This construction provides exceptional RF shielding exceeding 90 dB, ensuring minimal signal loss and interference. Encased in a durable PE jacket, the cable promises a service life of over 20 years and withstands more than 500 mating cycles.

Weighing 2050 grams, this 20m cable assembly is compliant with ISO 9001 Quality Management and RoHS certifications, reflecting its high quality and environmental responsibility. It includes 4.3-10 Male connectors on both ends, featuring a...

Read More



Powertec

Powertec is a wireless technology manufacturer and systems integrator based in Australia. Operating since 1995, Powertec has grown to become the leading wireless technology distributor in its region, and a leading Infratech systems developer. Supporting over 1500 partners the company provides procurement, design, project management, and support services across Australia, New Zealand, Pacific ...

RF Specification

Start Frequency
0 GHz
Stop Frequency
6 GHz

Physical Specification

Subtype
Feeder Cable
Mating Cycles
> 500
Compliance/Certifications
ISO 9001 Quality Management
,
RoHS
Length
20 m
Weight
2050 g

RF Connectors

RF Interface	Body Shape	Mounting
4.3-10 Male	Straight	Free Hanging
4.3-10 Male	Straight	Free Hanging

PTL-400

Min. Frequency
0 GHz
Impedance
50 Ω
Min. Bend Radius Static
25.4 mm
Min. Bend Radius Dynamic
101.6 mm
Max. Frequency
6 GHz
Shielding Effectiveness
> 90 dB
Colour
Black
Weight (g/m)
100 g
Cable Layers

Layer	Diameter	Materials
Inner Conductor	2.74 mm	Copper Clad Aluminium (CCA)
Dielectric	7.24 mm	Foamed Polyethylene (EPE)
Outer Conductor	7.39 mm	Aluminium Foil (Bonded)
Outer Conductor	8.13 mm	Tinned Copper Braid (TC), Tinned Copper Clad AlMg
Outer Jacket	10.29 mm	Polyethylene (PE)

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE

INFORMATION.

