

Powertec Wireless Technology ABN: 42 082 948 463 PO Box 1034, Ashmore City Queensland, Australia, 4214 sales@powertec.com.au 1300 769 378

# PTL-240 Coaxial Cable SMA Male to SMA Male 50cm

SKU: ACC-PT-00362 MPN: CA-P240-431SA1.50 Barcode: 9337692002687

#### Description

This short 50 cm jumper cable is used to interconnect two passive components that have SMA Female interfaces, such as a repeater to a surge protector or power divider.

Powertec's PTL-240 coaxial cable is a low loss RF cable with a medium-sized 6.10 mm outer diameter. This series is without a doubt the most popular choice of RF cable, due to its efficient compromise between performance and cost.

PTL-240 cable provides the flexibility and easy installation of a smaller diameter cable, with the low attenuation and shielding advantages of a larger cable. The cable is a mid-size providing a compromise between form-factor/bend radius, and attenuation/power handling. Its double shielded outer conductor provides exceptional RF shielding exceeding 90 dB, and PE jacket for a service life in excess of 20 years.



Read More



#### Powertec

Powertec is a wireless technology manufacturer and systems integrator based in Australia. Operating since 1995, Powertec has grown to become the leading wireless technology distributor in its region, and a leading Infratech systems developer. Supporting over 1500 partners the company provides procurement, design, project management, and support services across Australia, New Zealand, Pacific ...

## **RF** Specification

Start Frequency:	0 GHz	Stop Frequency:	6 GHz

## **Physical Specification**

Subtype:	Patch Cable	Length:	0.5 m
Mating Cycles:	> 500	Weight:	75 g
Compliance/Certifications:	ISO 9001 Quality Management		
RoHS	1		

#### **RF** Connectors

RF Interface	Body Shape	Mounting
N Male	Straight	Free Hanging
SMA Male	Straight	Free Hanging

### PTL-240

Min. Frequency:	0 GHz	Max. Frequency:	6 GHz
Impedance:	50	Shielding Effectiveness:	> 90 dB
Min. Bend Radius Static:	19.1 mm	Colour:	Black
Min. Bend Radius Dynamic:	63.5 mm	Weight (g/m):	50 g

## Cable Layers

Layer	Diameter	Materials
Inner Conductor	1.42 mm	Solid Copper
Dielectric	3.81 mm	Foamed Polyethylene (EPE)
Outer Conductor	3.94 mm	Aluminium Foil
Outer Conductor	4.52 mm	Tinned Copper Braid (TC)
Outer Jacket	6.10 mm	Polyethylene (PE)

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

