

Powertec Wireless Technology ABN: 42 082 948 463 PO Box 1034, Ashmore City Queensland, Australia, 4214 sales@powertec.com.au 1300 769 378

PTL-400 Coaxial Cable 4.3-10 Male to SMA Male 30m

SKU: IBC-PT-00016

MPN: CA-P400-431SA1.30 Barcode: 9337692002304

Description

The PTL-400 Coaxial Cable (SKU: IBC-PT-00016) from Powertec is a high-performance RF cable designed for wireless communication systems. This 30m cable features a 4.3-10 Male to SMA Male connection and belongs to the PTL-400 series, known for its low-loss properties and durability.

With a 10.29 mm outer diameter, the PTL-400 supports frequencies up to 6 GHz, making it ideal for entry- to intermediate-level systems. The cable's flexible design includes a double outer conductor made of aluminium tape and tinned copper braiding, offering RF shielding that exceeds 90 dB. Its PE jacket ensures a service life surpassing 20 years.

The cable is robust, enduring over 500 mating cycles, and complies with ISO 9001 Quality Management and RoHS certifications. It features a straight body shape and free-hanging mounting style for both connectors, ensuring ease of installation.

Powertec, an Australian company established in 1995, has grown into a leading...

Read More





Powertec

Powertec is a wireless technology manufacturer and systems integrator based in Australia. Operating since 1995, Powertec has grown to become the leading wireless technology distributor in its region, and a leading Infratech systems developer. Supporting over 1500 partners the company provides procurement, design, project management, and support services across Australia, New Zealand, Pacific ...

RF Specification

Start Frequency:	0 GHz	Stop Frequency:	6 GHz	

Physical Specification

Subtype:	Feeder Cable	Length:	30 m
Mating Cycles:	> 500	Weight:	3050 g
Compliance/Certifications:	ISO 9001 Quality Management		
RoHS	,		

RF Connectors

RF Interface	Body Shape	Mounting
4.3-10 Male	Straight	Free Hanging
SMA Male	Straight	Free Hanging

PTL-400

Min. Frequency:	0 GHz	Max. Frequency:	6 GHz
Impedance:	50	Shielding Effectiveness:	> 90 dB
Min. Bend Radius Static:	25.4 mm	Colour:	Black
Min. Bend Radius Dynamic:	101.6 mm	Weight (g/m):	100 g

Cable Layers

Layer	Diameter	Materials
Inner Conductor	2.74 mm	Copper Clad Aluminium (CCA)
Dielectric	7.24 mm	Foamed Polyethylene (EPE)
Outer Conductor	7.39 mm	Aluminium Foil (Bonded)
Outer Conductor	8.13 mm	Tinned Copper Braid (TC), Tinned Copper Clad AIMg
Outer Jacket	10.29 mm	Polyethylene (PE)

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

