

Powertec Wireless Technology ABN: 42 082 948 463 PO Box 1034, Ashmore City Queensland, Australia, 4214 sales@powertec.com.au 1300 769 378

Powertec RF Directional Coupler, 20 dB, 698-3800 MHz, 4.3-10 Female, -155 dBc

SKU: IBC-PT-00027

MPN: PCM-DC20-6940.432 Barcode: 9337692001642

Description

The Powertec RF Directional Coupler (SKU: IBC-PT-00027), part number PCM-DC20-6940.432, is designed for efficient RF signal management in the frequency range of 698 to 3800 MHz. With a coupling value of 20 dB, this coupler ensures reliable performance in various wireless communication applications. Its compact dimensions are 129x23.5x48 mm, making it suitable for space-constrained installations.

Featuring an IP65 ingress protection rating, the coupler is built to withstand challenging environments, operating effectively between -25 °C and 75 °C. The 4.3-10 Female connectors on the input, output, and coupled ports provide robust connectivity. Its electrical performance includes a 3rd Order PIM rating of -155 dBc and an input impedance of 50 Ω .

The coupler demonstrates a VSWR of less than 1.3:1, an Insertion Loss of 0.40 dB, and Inter-Port Isolation greater than 33 dB, ensuring minimal signal degradation and high isolation between ports.

Man...

Read More





Powertec

Powertec is a wireless technology manufacturer and systems integrator based in Australia. Operating since 1995, Powertec has grown to become the leading wireless technology distributor in its region, and a leading Infratech systems developer. Supporting over 1500 partners the company provides procurement, design, project management, and support services across Australia, New Zealand, Pacific ...

RF Specification

Min. Frequency:	698 MHz	Input Impedance:	50
Max. Frequency:	3800 MHz	Max. Input Power:	300 W
Coupling / Split:	20 dB	PIM, 3rd Order:	-155 dBc

Port Matrix


Port Function	RF Interface
Input	4.3-10 Female
Output	4.3-10 Female
Coupled	4.3-10 Female

Frequency Test Data

Start Frequency	Stop Frequency	VSWR	Insertion Loss	Inter-Port Iso.
698 MHz	3800 MHz	< 1.3:1	0.4 dB	> 33 dB

Physical Specification

1	Min. Operating Temperature:	-25 °C
2	Max. Operating Temperature:	75 °C
Directional Coupler		
IP65		
129x23.5x48		
0.38 kg		
	Directional Coupler IP65 129x23.5x48	2 Max. Operating Temperature: Directional Coupler IP65 129x23.5x48



Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

