

Powertec RF Attenuator, 15 dB, 4.3-10 Female to Male

SKU: IBC-PT-00030

MPN: PCM-AT15-DC38.432

Barcode: 9337692001673

Description

The Powertec RF Attenuator (SKU: IBC-PT-00030, Part Number: PCM-AT15-DC38.432) offers a reliable solution for RF signal management with a 15 dB attenuation across a wide frequency range from 0 MHz to 3000 MHz. Designed for robust applications, it features 4.3-10 female to male connectors and an IP60 ingress protection rating, ensuring strong performance in various environments. With dimensions of 60 x 19.5 mm, the attenuator is compact yet durable, making it suitable for diverse installations.

Operating efficiently within a temperature range of -35 °C to 65 °C, it meets demanding conditions while maintaining an input impedance of 50 Ω. This product is ideal for applications requiring precise signal attenuation in wireless communication systems. Manufactured by Powertec, a leading Australian company renowned for its expertise in cellular network enhancement and wireless network development, this attenuator reflects the company's...

[Read More](#)



Powertec

Powertec is a wireless technology manufacturer and systems integrator based in Australia. Operating since 1995, Powertec has grown to become the leading wireless technology distributor in its region, and a leading Infratech systems developer. Supporting over 1500 partners the company provides procurement, design, project management, and support services across Australia, New Zealand, Pacific ...

RF Specification

| | | | |
|----------------------|----------|-------------------|-----|
| Min. Frequency: | 0 MHz | Input Impedance: | 50 |
| Max. Frequency: | 3000 MHz | Max. Input Power: | 5 W |
| Attenuation (Fixed): | 15 dB | | |

Port Matrix

| Port Label | Port Function | RF Interface |
|------------|---------------|--------------|
|------------|---------------|--------------|


Frequency Test Data

| Start Frequency | Stop Frequency | VSWR | Insertion Loss | Inter-Port Iso. | Return Loss |
|-----------------|----------------|------|----------------|-----------------|-------------|
|-----------------|----------------|------|----------------|-----------------|-------------|

Physical Specification

| | | | |
|---------------------|------------|-----------------------------|--------|
| Subtype: | Attenuator | Min. Operating Temperature: | -35 °C |
| Ingress Protection: | IP60 | Max. Operating Temperature: | 65 °C |
| Dimensions: | 60 x 19.5 | | |
| Weight: | 0.1 kg | | |

Drawing



Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

