

Powertec Wireless Technology ABN: 42 082 948 463 PO Box 1034, Ashmore City Queensland, Australia, 4214 sales@powertec.com.au 1300 769 378

# Powertec 5W Attenuator, 5dB, 698 to 3800 MHz, 4.3-10 Female to Male, -155 dBc

SKU: IBC-PT-00049 MPN: PCM-AT5-DC38.432 Barcode: 9337692001864

### Description

The Powertec 5W Attenuator (SKU: IBC-PT-00049) is a highquality RF passive component, designed for applications within the 698 to 3800 MHz frequency range. It offers a consistent attenuation value of 5 dB, ensuring reliable signal reduction. The attenuator features a 4.3-10 Male to Female connector configuration, making it versatile for various installations. It boasts a low VSWR of 1.2:1, ensuring minimal signal reflection and optimal performance.

Constructed with durability in mind, this component measures 60x19.5 mm and is rated IP60 for environmental protection. It operates efficiently in temperatures ranging from -35 °C to 65 °C, making it suitable for diverse environmental conditions. The input impedance is 50  $\Omega$ , aligning with standard RF systems.

Manufactured by Powertec in Australia, the attenuator is part of the PCM-AT5-DC38.432 series. Powertec, established in 1995, is a leader in wireless technology distribution and...







#### Powertec

Powertec is a wireless technology manufacturer and systems integrator based in Australia. Operating since 1995, Powertec has grown to become the leading wireless technology distributor in its region, and a leading Infratech systems developer. Supporting over 1500 partners the company provides procurement, design, project management, and support services across Australia, New Zealand, Pacific ...

## **RF** Specification

Min. Frequency:	698 MHz	Input Impedance:	50			
Max. Frequency:	3800 MHz	Max. Input Power:	5 W			
Attenuation (Fixed):	5 dB					
Port Matrix						
Port Function		R	RF Interface			
Input		4.	4.3-10 Male			
Output		4.3	4.3-10 Female			
Frequency Test Data						
VSWR						
< 1.2:1						

### **Physical Specification**

Input Ports:	1	Min. Operating Temperature:	-35 °C
Output Ports:	1	Max. Operating Temperature:	65 °C
Subtype:	Attenuator		
Ingress Protection:	IP60		
Dimensions:	60x19.5		
Weight:	0.1 kg		

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

