

PSF-402 Patch Cable 4.3-10 Female to SMA Male 30cm

SKU: IBC-PT-00069
 MPN: CA-R402-432SA1.030
 Barcode: 9337692001994

Description

The PSF-402 Patch Cable by Powertec (SKU: IBC-PT-00069, Part Number: CA-R402-432SA1.030) is a high-performance RF coaxial cable, ideal for component interconnections requiring reliable and low-loss signal transmission. This 0.141" semi-flexible cable features a bright blue 4.2 mm outer jacket, providing excellent shielding with its tin-soaked copper braid. It supports frequencies up to 34 GHz, making it an efficient choice for applications balancing performance and cost.


Measuring 30 cm in length and weighing 58 g, the cable is designed to endure over 500 mating cycles, with an operational frequency range from 0 to 6 GHz. Its flexible nature allows for easy forming and immediate bends behind the fillet, reducing the likelihood of solder joint failures. The PSF-402 series offers variations in different colours for easy identification of radio chains.

The cable is equipped with a 4.3-10 Female connector on one end and an SMA Male connector...

[Read More](#)



RF Specification

<p>Start Frequency: </p> <p>VSWR Measurement</p>	<p>Powertec 0 GHz</p> <p><small>Powertec is a wireless technology manufacturer and systems integrator based in Australia. Operating since 1995, Powertec has grown to become the leading wireless technology distributor in its region, and a leading Infratech systems developer. Supporting over 1500 partners the company provides procurement, design, project management, and support services across Australia, New Zealand, Pacific ...</small></p> <p>Frequency 6000 MHz</p>	<p>Stop Frequency: 6 GHz</p> <p>VSWR ≤ 1.5:1</p>
---	--	---


Physical Specification

Subtype:	Patch Cable	Length:	0.3 m
Mating Cycles:	> 500	Weight:	58 g
Compliance/Certifications:	ISO 9001 Quality Management		
RoHS			

RF Connectors

RF Interface	Body Shape	Mounting
4.3-10 Female	Straight	Free Hanging
SMA Male	Straight	Free Hanging

Drawing



PSF-402

Min. Frequency:	0 GHz	Max. Frequency:	34 GHz
Impedance:	50	Shielding Effectiveness:	> 110 dB
Min. Bend Radius Static:	8 mm	Colour:	Blue
Min. Bend Radius Dynamic:	40 mm		

Cable Layers

Layer	Diameter	Materials
Inner Conductor	0.93 mm	Silver Plated Copper (SC)
Dielectric	3.00 mm	PTFE / Teflon
Outer Conductor	3.52 mm	Tin Soaked Copper Braid
Outer Jacket	4.20 mm	Polyolefin LSZH

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

