

PSF-402 Patch Cable 4.3-10 Female to SMA Male 50cm

SKU: IBC-PT-00070

MPN: CA-R402-432SA1.050

Barcode: 9337692001734

Description

The PSF-402 Patch Cable, part number CA-R402-432SA1.050, is a high-performance RF cable developed by Powertec. This cable features a PSF-402 type, 0.141" semi-flexible design, offering a balance of performance and cost efficiency. With a bright blue 4.2 mm outer jacket, it supports frequencies up to 34 GHz, making it ideal for component interconnections.

The cable's structure includes a tin-soaked copper braid, providing nearly 100% RF shielding, and a malleable outer jacket to prevent solder joint failures, allowing for bends directly behind the fillet. It measures 50 cm in length and weighs 63 grams. The patch cable is designed to endure over 500 mating cycles within an operating frequency range of 0 GHz to 6 GHz.

Connectivity is provided by a 4.3-10 Female connector on one end and an SMA Male connector on the other, both featuring straight body shapes and free-hanging mounting styles. The cable offers a VSWR of $\leq 1.5:1$ at 6000 MHz...

[Read More](#)



Powertec

Powertec is a wireless technology manufacturer and systems integrator based in Australia. Operating since 1995, Powertec has grown to become the leading wireless technology distributor in its region, and a leading Infratech systems developer. Supporting over 1500 partners the company provides procurement, design, project management, and support services across Australia, New Zealand, Pacific ...

RF Specification

Start Frequency: 0 GHz Stop Frequency: 6 GHz

VSWR Measurement

Frequency	VSWR
6000 MHz	$\leq 1.5:1$

Physical Specification

Subtype: Patch Cable Length: 0.5 m

Mating Cycles: > 500 Weight: 63 g

Compliance/Certifications: ISO 9001 Quality Management

RoHS

RF Connectors

RF Interface

4.3-10 Female

SMA Male

Body Shape

Straight


Straight

Mounting

Free Hanging

Free Hanging

Drawing



PSF-402

Min. Frequency:	0 GHz	Max. Frequency:	34 GHz
Impedance:	50	Shielding Effectiveness:	> 110 dB
Min. Bend Radius Static:	8 mm	Colour:	Blue
Min. Bend Radius Dynamic:	40 mm		

Cable Layers

Layer	Diameter	Materials
Inner Conductor	0.93 mm	Silver Plated Copper (SC)
Dielectric	3.00 mm	PTFE / Teflon
Outer Conductor	3.52 mm	Tin Soaked Copper Braid
Outer Jacket	4.20 mm	Polyolefin LSZH

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

