

Page



Powertec Wireless Technology
ABN: 42 082 948 463
PO Box 1034, Ashmore City
Queensland, Australia, 4214
sales@powertec.com.au
1300 769 378

PSF-402 Patch Cable 4.3-10 Female to SMA Male 1m

SKU
IBC-PT-00071
MPN
CA-R402-432SA1.1
Barcode
9337692001987

Description

The PSF-402 Patch Cable, part number CA-R402-432SA1.1, is a high-performance RF cable developed by Powertec, ideal for various component interconnections. With a length of 1 metre and weighing 75 grams, it features a PSF-402 coaxial cable type, known for its 0.141" semi-flexible low-loss design and bright blue 4.2 mm outer jacket. This cable supports frequencies up to 34 GHz and offers an exceptional balance between performance and cost.

Engineered for durability, the PSF-402 cable withstands over 500 mating cycles and ensures excellent RF shielding due to its tin-soaked copper braid construction. Its malleable jacket design prevents solder joint failures and allows for immediate bends behind the fillet. The cable is hand-formable and provides mode-free operation up to 34 GHz, making it suitable for microwave-grade applications.

Connectivity is ensured through a 4.3-10 Female connector and an SMA Male connector, both featuring a Straight...

[Read More](#)





Powertec

Powertec is a wireless technology manufacturer and systems integrator based in Australia. Operating since 1995, Powertec has grown to become the leading wireless technology distributor in its region, and a leading Infratech systems developer. Supporting over 1500 partners the company provides procurement, design, project management, and support services across Australia, New Zealand, Pacific ...

RF Specification

Start Frequency

0 GHz

Stop Frequency

6 GHz

VSWR Measurement

Frequency VSWR

6000 MHz $\leq 1.5:1$

Physical Specification

Subtype

[Patch Cable](#)

Mating Cycles

> 500

Compliance/Certifications

[ISO 9001 Quality Management](#)

,

[RoHS](#)


Length
1 m
Weight
75 g

RF Connectors

RF Interface Body Shape Mounting

[4.3-10 Female Straight](#) [Free Hanging](#)
[SMA Male](#) [Straight](#) [Free Hanging](#)

Drawing



PSF-402

Min. Frequency
0 GHz
Impedance
50 Ω
Min. Bend Radius Static
8 mm
Min. Bend Radius Dynamic
40 mm
Max. Frequency
34 GHz
Shielding Effectiveness
> 110 dB
Colour
Blue
Cable Layers

Layer	Diameter	Materials
Inner Conductor	0.93 mm	Silver Plated Copper (SC)
Dielectric	3.00 mm	PTFE / Teflon
Outer Conductor	3.52 mm	Tin Soaked Copper Braid
Outer Jacket	4.20 mm	Polyolefin LSZH

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

