

Page



Powertec Wireless Technology
ABN: 42 082 948 463
PO Box 1034, Ashmore City
Queensland, Australia, 4214
sales@powertec.com.au
1300 769 378

Powertec 3x3 Hybrid Combiner, 698 to 3800 MHz, 4.3-10 Female, -155 dBc

SKU
IBC-PT-00076
MPN
PCM-HY3-6938.432
Barcode
9337692002731

Description

The Powertec 3x3 Hybrid Combiner (SKU: IBC-PT-00076) is a high-performance RF passive component designed for seamless integration in various wireless applications. Operating within a broad frequency range from 698 to 3800 MHz, this combiner ensures optimal signal management with its robust specifications. Measuring 244.4 x 125 x 41 mm, it features a durable construction with an IP67 ingress protection rating, making it suitable for outdoor installations.

Key electrical features include a 3rd Order PIM rating of -155 dBc and a standard input impedance of 50 Ω , ensuring minimal signal distortion and high-quality transmission. The unit boasts a VSWR of less than 1.3:1, a return loss of ≤ 18.00 dB, an insertion loss of 6.00 dB, and inter-port isolation of over 23 dB, providing exceptional performance across its operating frequencies.

Equipped with 4.3-10 Female connectors on both input and output ports, this RoHS-compliant hybrid coupler...

[Read More](#)





Powertec

Powertec is a wireless technology manufacturer and systems integrator based in Australia. Operating since 1995, Powertec has grown to become the leading wireless technology distributor in its region, and a leading Infratech systems developer. Supporting over 1500 partners the company provides procurement, design, project management, and support services across Australia, New Zealand, Pacific ...

RF Specification

Min. Frequency

698 MHz

Max. Frequency

3800 MHz

Input Impedance

50 Ω

Max. Input Power

500 W

PIM, 3rd Order

-155 dBc

Port Matrix

Port Function RF Interface

Input [4.3-10 Female](#)

Output [4.3-10 Female](#)

Frequency Test Data

**Start
Frequency**

**Stop
Frequency**

VSWR

**Insertion
Loss**

**Inter-Port
Iso.**

**Return
Loss**

698 MHz

3800 MHz

<
1.3:1

6 dB

> 23 dB

≤ 18 dB

Physical Specification

Input Ports

3

Output Ports

3

Subtype

[Hybrid Coupler](#)

Ingress Protection

[IP67](#)

Dimensions

244.4 x 125 x 41

Weight

2.3 kg

Min. Operating Temperature

-25 °C


Max. Operating Temperature

70 °C

Compliance/Certifications

[RoHS](#)

Drawing



Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

