

RG-402 Patch Cable 4.3-10 Male to QMA Male Right Angle 50cm

SKU: IBC-PT-00078

MPN: CA-R402-431QA1RA.050

Barcode: 9337692004841

Description



RF Specification

Start Frequency: 0 GHz Stop Frequency: 6 GHz

Physical Specification

Subtype: Patch Cable Length: 0.5 m

Mating Cycles: > 500 Weight: 63 g

Compliance/Certifications: ISO 9001 Quality Management

RoHS

RF Connectors

RF Interface

4.3-10 Male

QMA Male

Body Shape

Straight

Right Angle

Mounting

Free Hanging

Free Hanging

PSF-402

Min. Frequency: 0 GHz Max. Frequency: 34 GHz

Impedance: 50 Shielding Effectiveness: > 110 dB

Min. Bend Radius Static: 8 mm Colour: Blue

Min. Bend Radius Dynamic: 40 mm

Cable Layers

Layer	Diameter	Materials
Inner Conductor	0.93 mm	Silver Plated Copper (SC)
Dielectric	3.00 mm	PTFE / Teflon
Outer Conductor	3.52 mm	Tin Soaked Copper Braid
Outer Jacket	4.20 mm	Polyolefin LSZH

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

