

PSF-402 Patch Cable 4.3-10 Male to 4.3-10 Male Low PIM 1m

SKU: IBC-PT-00090

MPN: CA-R402-431431.1

Barcode: 9337692002809

Description



RF Specification

Start Frequency:

0 GHz

Stop Frequency:

6 GHz

Physical Specification



Powertec

Powertec is a wireless technology manufacturer and systems integrator based in Australia. Operating since 1995, Powertec has grown to become the leading wireless technology distributor in its region, and a leading Infratech systems developer. Supporting over 1500 partners the company provides procurement, design, project management, and support services across Australia, New Zealand, Pacific ...

Subtype:	Jumper Cable	Length:	1 m
Mating Cycles:	> 500	Weight:	75 g
Compliance/Certifications:	ISO 9001 Quality Management		
RoHS			

RF Connectors

RF Interface	Body Shape	Mounting
4.3-10 Male	Straight	Free Hanging
4.3-10 Male	Straight	Free Hanging

PSF-402

Min. Frequency:	0 GHz	Max. Frequency:	34 GHz
Impedance:	50	Shielding Effectiveness:	> 110 dB
Min. Bend Radius Static:	8 mm	Colour:	Blue
Min. Bend Radius Dynamic:	40 mm		

Cable Layers

Layer	Diameter	Materials
Inner Conductor	0.93 mm	Silver Plated Copper (SC)
Dielectric	3.00 mm	PTFE / Teflon
Outer Conductor	3.52 mm	Tin Soaked Copper Braid
Outer Jacket	4.20 mm	Polyolefin LSZH

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

