

Powertec Wireless Technology ABN: 42 082 948 463 PO Box 1034, Ashmore City Queensland, Australia, 4214 sales@powertec.com.au 1300 769 378

# MARS 4G Panel Antenna, 5dBi, 698 to 2700 MHz, N Female

SKU: ANT-MA-00004 MPN: MA-CLTE-14B

#### Description

The MARS 4G Panel Antenna (SKU: ANT-MA-00004) is a versatile solution designed for a wide range of wireless applications, including LTE, WiMAX, Cellular, and Wi-Fi systems. Operating within the 698 to 2700 MHz frequency range, this antenna features a peak gain of up to 6.5 dBi, ensuring robust performance across various bands. The unit is housed in a durable polycarbonate enclosure with an IP65 rating, offering excellent protection against harsh environmental conditions.

This antenna is equipped with a single N Female RF connection, supporting up to 10 W of input power and maintaining a 50  $\Omega$  impedance. Its linear polarisation and compliant with RoHS standards, make it suitable for both fixed and mobile, standalone or embedded applications. The MARS 4G Panel Antenna is engineered to meet IEC 60068-2-11: Salt Mist standards, ensuring reliability in challenging environments.

Manufactured by MARS Antennas, a leader in antenna design and RF...

Read More



#### MARS Antennas

MARS Antennas & RF Systems is a world class antennas design and manufacturer, RF solutions provider and R&D Company with a proven capacity to design and provide cost effective products with exceptional performance. Since 1994, MARS has been specializing in Outdoor & In-Building Multi Polarized Antennas. MARS subscriber & base station antennas are used in LTE, WiMAX, Cellular, Mobile, MIMO, WLAN ...

## **RF** Specification

Start Frequency:	698 MHz	Polarisation:	Linear
Stop Frequency:	2270 MHz	Input Impedance:	50
Max. Input Power:	10 W		

## **RF** Connectors

Ports	RF Interface	Body Shape
1	N Female	Straight

## Frequency Test Data

Start Freq.	Stop Freq.	Peak Gain	VSWR	Azimuth	Elevation
698 MHz	806 MHz	5 dBi	< 2:1	130°	70°
806 MHz	960 MHz	6 dBi	< 2:1	140°	60°
1710 MHz	2170 MHz	6.5 dBi	< 1.7:1	80°	45°
2200 MHz	2270 MHz	5 dBi	< 1.7:1	55°	30°

## **Physical Specification**

Subtype:	Panel / Sector	Dimensions:	231 x 215 x 37.5
Input Ports:	1	Ingress Protection:	IP65
MIMO:	1x1 SISO	Materials:	Plastic, Polycarbonate (PC)
Min. Operating Temperature:	-40 °C	Weight:	0.5 kg
Max. Operating Temperature:	65 °C	Compliance/Certifications:	RoHS
		Mechanical Compliance:	IEC 60068-2-11: Salt Mist

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

