

Page



Powertec Wireless Technology
ABN: 42 082 948 463
PO Box 1034, Ashmore City
Queensland, Australia, 4214
sales@powertec.com.au
1300 769 378

CommScope HELIAX 1/2" SureFlex Jumper with interface types 4.3-10 Male and 4.3-10 Male, 1m

SKU
ACC-CS-00099
MPN
F4A-HPMHM-1M

Description

The CommScope HELIAX 1/2" SureFlex Jumper (SKU: ACC-CS-00099) is a robust RF coaxial cable designed for large antenna systems, including passive Distributed Antenna Systems. This 1m jumper features 4.3-10 Male connectors on both ends, ensuring consistent performance with a straight body shape and free-hanging mounting style.

Constructed with a solid corrugated copper outer conductor, this 1/2" cable offers superior shielding effectiveness of 110 dB and low Passive Intermodulation (PIM) with a rating of -119 dBc. It supports an operating frequency range from 698 MHz to 3800 MHz, making it versatile for various applications. The cable's robust design withstands numerous mating cycles, ensuring reliable long-term use.

Performance metrics include a VSWR of $\leq 1.07:1$ and a Return Loss of ≤ 30.04 dB at frequencies ranging from 698 MHz to 1700 MHz. At 2200 MHz, the VSWR is $\leq 1.08:1$ with a Return Loss of ≤ 27.99 dB, and at 3400 MHz, a VSWR of $\leq 1...$

[Read More](#)





[CommScope](#)

CommScope (NASDAQ: COMM) helps design, build and manage wired and wireless networks around the world. As a communications infrastructure leader, we shape the always-on networks of tomorrow. For more than 40 years, our global team of greater than 20,000 employees, innovators and technologists have empowered customers in all regions of the world to anticipate what's next and push the boundaries of ...

RF Specification

Start Frequency

698 GHz

PIM, 3rd Order

-119 dBc

Stop Frequency

3800 GHz

VSWR Measurement

Frequency	VSWR	Return Loss
-----------	------	-------------

698 MHz	$\leq 1.07:1$	≤ 30.04 dB
---------	---------------	-----------------

1700 MHz	$\leq 1.07:1$	≤ 30.04 dB
----------	---------------	-----------------

2200 MHz	$\leq 1.08:1$	≤ 27.99 dB
----------	---------------	-----------------

3400 MHz	$\leq 1.22:1$	≤ 20.01 dB
----------	---------------	-----------------

Physical Specification

Subtype

[Jumper Cable](#)

Compliance/Certifications

[ISO 9001 Quality Management](#)

,

[RoHS](#)

Length

1 m

RF Connectors

RF Interface Body Shape Mounting

[4.3-10 Male](#) [Straight](#) [Free Hanging](#)

[4.3-10 Male](#) [Straight](#) [Free Hanging](#)

[RSJ4-50](#)

Min. Frequency

0 GHz

Impedance

50 Ω

Min. Bend Radius Static

31.75 mm

Min. Bend Radius Dynamic

31.75 mm

Max. Frequency

10.2 GHz

Colour

Black

Weight (g/m)

150 g

Cable Layers

Layer	Diameter	Materials
Inner Conductor	3.59 mm	Copper Clad Aluminium (CCA)
Dielectric	9.42 mm	Foamed Polyethylene (EPE)
Outer Conductor	11.99 mm	Corrugated Copper Tube
Outer Jacket	13.41 mm	Polyethylene (PE)

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual

property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

