

# CommScope HELIAX 1/2" SureFlex Jumper with interface types 4.3-10 Male and 4.3-10 Male, 1m

SKU: ACC-CS-00099

MPN: F4A-HPHMHM-1M

## Description

The CommScope HELIAX 1/2" SureFlex Jumper (SKU: ACC-CS-00099) is a robust RF coaxial cable designed for large antenna systems, including passive Distributed Antenna Systems. This 1m jumper features 4.3-10 Male connectors on both ends, ensuring consistent performance with a straight body shape and free-hanging mounting style.

Constructed with a solid corrugated copper outer conductor, this 1/2" cable offers superior shielding effectiveness of 110 dB and low Passive Intermodulation (PIM) with a rating of -119 dBc. It supports an operating frequency range from 698 MHz to 3800 MHz, making it versatile for various applications. The cable's robust design withstands numerous mating cycles, ensuring reliable long-term use.

Performance metrics include a VSWR of  $\leq 1.07:1$  and a Return Loss of  $\leq 30.04$  dB at frequencies ranging from 698 MHz to 1700 MHz. At 2200 MHz, the VSWR is  $\leq 1.08:1$  with a Return Loss of  $\leq 27.99$  dB, and at 3400 MHz, a VSWR of  $\leq 1...$

[Read More](#)



## RF Specification

Start Frequency:	698 GHz	Stop Frequency:	3800 GHz
PIM, 3rd Order:	-119 dBc		
VSWR Measurement	CommScope (NASDAQ: COMM) helps design, build and manage wired and wireless networks around the world. As a communications infrastructure leader, we shape the always-on networks of tomorrow. For more than 40 years, our global team of greater than 20,000 employees, innovators and technologists have empowered customers in all regions of the world to anticipate what's next and push the boundaries of ...		

Frequency	VSWR	Return Loss
698 MHz	≤ 1.07:1	≤ 30.04 dB
1700 MHz	≤ 1.07:1	≤ 30.04 dB
2200 MHz	≤ 1.08:1	≤ 27.99 dB
3400 MHz	≤ 1.22:1	≤ 20.01 dB

## Physical Specification

Subtype:	Jumper Cable	Length:	1 m
Compliance/Certifications:	ISO 9001 Quality Management		
RoHS			

### RF Connectors

RF Interface	Body Shape	Mounting
4.3-10 Male	Straight	Free Hanging
4.3-10 Male	Straight	Free Hanging

## RSJ4-50

Min. Frequency:	0 GHz	Max. Frequency:	10.2 GHz
Impedance:	50	Colour:	Black
Min. Bend Radius Static:	31.75 mm	Weight (g/m):	150 g
Min. Bend Radius Dynamic:	31.75 mm		

### Cable Layers

Layer	Diameter	Materials
Inner Conductor	3.59 mm	Copper Clad Aluminium (CCA)
Dielectric	9.42 mm	Foamed Polyethylene (EPE)
Outer Conductor	11.99 mm	Corrugated Copper Tube
Outer Jacket	13.41 mm	Polyethylene (PE)

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

