

Page



Powertec Wireless Technology
ABN: 42 082 948 463
PO Box 1034, Ashmore City
Queensland, Australia, 4214
sales@powertec.com.au
1300 769 378

Poynting CAB-109, 10M TWIN HDF- 195 Low Loss Cable

SKU
ANT-PY-00022
MPN
A-CAB-109

Description

The Poynting CAB-109 is a 10-metre, twin HDF-195 low loss coaxial cable designed for high-performance RF applications. Known by the part number A-CAB-109, this cable is engineered as a superior alternative to RG-58, RG-122, RG-303, and RG-142 cables. Its L-195 specification is synonymous with the LMR-195 designation, offering excellent RF shielding of over 90 dB due to its double-shielded conductor. The durable PE jacket ensures a service life exceeding 20 years, making it a reliable choice for long-term installations.

This cable supports operating frequencies from 0 GHz to 6 GHz and is compliant with CE and RoHS certifications, ensuring environmental and safety standards are met. It exhibits a VSWR of $\leq 1.35:1$ at 6000 MHz, indicative of superior signal integrity. Designed to endure multiple mating cycles, it is ideal for various applications including 4G LTE, GSM, Machine to Machine (M2M), Digital Television (DTV), and other...

[Read More](#)





Poynting

Poynting is a top global provider of integrated antenna solutions, responsible for the innovation, design and manufacture of its market-leading products.

Established as a consultancy in 1990, Poynting evolved into an official PTY in 1997 and in 2001 established Poynting Antennas. It caters antenna solutions for primarily wireless high speed data applications, including residential 4G LTE as well ...

RF Specification

Start Frequency

0 GHz

Stop Frequency

6 GHz

VSWR Measurement

Frequency VSWR

6000 MHz $\leq 1.35:1$

Physical Specification

Subtype

[Feeder Cable](#)

Compliance/Certifications

[CE](#)

,

[RoHS](#)

Length

10 m

RF Connectors

RF Interface Body Shape Mounting

SMA Female	Straight	Free Hanging
SMA Male	Straight	Free Hanging

L-195

Min. Frequency
0 GHz
Impedance
50 Ω
Min. Bend Radius Static
12.7 mm
Min. Bend Radius Dynamic
50.8 mm
Attenuation @ 1 GHz
0.39 dB/m
Max. Frequency
41 GHz
Shielding Effectiveness
> 90 dB
Colour
Black
Weight (g/m)
30 g
Cable Layers

Layer	Diameter	Materials	Notes
Inner Conductor	0.94 mm	Solid Copper	Some cable variants have a stranded inner conductor
Dielectric	2.79 mm	Foamed Polyethylene (EPE)	
Outer Conductor	2.95 mm	Aluminium Foil (Bonded)	
Outer Conductor	3.53 mm	Tinned Copper Braid (TC)	
Outer Jacket	4.95 mm	Polyethylene (PE)	

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

