

Page



Powertec Wireless Technology  
ABN: 42 082 948 463  
PO Box 1034, Ashmore City  
Queensland, Australia, 4214  
sales@powertec.com.au  
1300 769 378

## **Poynting XPOL-1-5G, Omni- Directional, 2x2 MIMO 4G-5G antenna; 617 to 3800 MHz**

SKU  
ANT-PY-00012  
MPN  
A-XPOL-0001-V2-21  
Barcode  
6009710920886

## Description

The Poynting XPOL-1-5G is an omni-directional, 2x2 MIMO antenna designed to enhance 4G and 5G connectivity across a broad frequency range of 617 to 3800 MHz. Constructed from durable ASA plastic, this dipole antenna is compact, measuring 247 x 157 x 88 mm, and weighs just 0.95 kg. Its robust design boasts an IP65 ingress protection rating, ensuring reliable performance in challenging environments with temperatures from -40°C to 70°C.

Equipped with two RF connections via SMA Male interfaces, the XPOL-1-5G supports a 50  $\Omega$  impedance and up to 20 W input power, delivering a peak gain of 3.0 dBi and maintaining a VSWR of less than 2.5:1. Its 360° azimuth beamwidth ensures comprehensive coverage, making it ideal for applications requiring consistent and widespread signal distribution.

This antenna is perfect for enhancing wireless high-speed data applications, including residential 4G LTE, GSM, M2M, DTV, and customer premise equipment. It...

[Read More](#)



## [Poynting](#)

Poynting is a top global provider of integrated antenna solutions, responsible for the innovation, design and manufacture of its market-leading products.

Established as a consultancy in 1990, Poynting evolved into an official PTY in 1997 and in 2001 established Poynting Antennas. It caters antenna solutions for primarily wireless high speed data applications, including residential 4G LTE as well ...

# RF Specification

Start Frequency

698 MHz

Stop Frequency

3800 MHz

Max. Input Power

20 W

Polarisation

[Linear](#)

Input Impedance

50  $\Omega$

RF Connectors

Ports	RF Interface	Body Shape	Cable Series	Length
-------	--------------	------------	--------------	--------

1	<a href="#">SMA Male</a>	<a href="#">Straight</a>	<a href="#">L-195</a>	5000 mm
---	--------------------------	--------------------------	-----------------------	---------

Frequency Test Data

Start Freq.	Stop Freq.	Peak Gain	VSWR	Azimuth
-------------	------------	-----------	------	---------

698 MHz	3800 MHz	3 dBi	< 2.5:1	360°
---------	----------	-------	---------	------

# Physical Specification

Subtype

[Dipole](#)

Input Ports

2

MIMO

[2x2 MIMO](#)

Min. Operating Temperature

-40 °C

Max. Operating Temperature

70 °C

Dimensions

247 x 157 x 88

Ingress Protection

[IP65](#)

Materials

[ASA Plastic](#)

Weight

0.95 kg

Compliance/Certifications

CE

,

RoHS

,

ISO 9001 Quality Management

Mechanical Compliance

MIL-STD-810: Environmental Durability

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

