

TNC Male Connector L-400 Coaxial Cable

SKU: ACC-PT-00061
 MPN: TN1-C-L40
 Barcode: 9337692003387

Description

While considered an older design, TNC connectors remain widely used in many US-manufactured devices. Within the wireless communications industry the most popular device manufacturer using TNC connectors is Cisco, who almost exclusively use the connector on its 5G and LTE-HWIC mobile broadband modules.

The TNC Male crimp for L-400 cables is very simple to fit-off. After preparing the PTL-400 (or equivalent series) cable, the connector's centre pin is soldered to the cables inner conductor, and the outer body simply slides over the top until the pin is fully inserted and the body cannot be pushed on any further. The ferrule is crimped using a standard 10.89 mm (.429") hex die.



Read More

TNC Male connectors remain highly popular on a range of Cisco cellular modems, industrial SCADA and ICS radios, and 900 MHz packet data transmitters.

RF Connector Interface

RF Interface	Body Shape	Mounting
TNC Male	Straight	Free Hanging

RF Specification



Powertec

Powertec is a wireless technology manufacturer and systems integrator based in Australia. Operating since 1995, Powertec has grown to become the leading wireless technology distributor in its region, and a leading Infratech systems developer. Supporting over 1500 partners the company provides procurement, design, project management, and support services across Australia, New Zealand, Pacific ...

Start Frequency:	0 GHz	Input Impedance:	50
Stop Frequency:	4 GHz	Inner Contact Resistance:	$\leq 1 \text{ m}\Omega$
		Insulation Resistance:	$\geq 5000 \text{ m}\Omega$
		Outer Contact Resistance:	$\leq 1 \text{ m}\Omega$
		RF Operating Voltage:	$\leq 500 \text{ Vrms}$

VSWR Measurement

Frequency	VSWR
4000 MHz	$\leq 1.25:1$

Physical Specification

Cable Group:	L-400	Conductor Attachment:	Cable, Crimp
Body Material:	Brass	Contact Material:	Brass
Body Plating:	Nickel	Contact Plating:	Gold
Insulator Material:	PTFE / Teflon	Min. Operating Temperature:	$-40 \text{ }^\circ\text{C}$
Dimensions:	$26 \times 15 \times 15$	Max. Operating Temperature:	$85 \text{ }^\circ\text{C}$
Weight:	18.7 g	Mating Cycles:	> 500
Compliance/Certifications:	ISO 9001 Quality Management		

RoHS

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

