

# Huang Liang SMA Male to SMA Female Radius RA Adapter, Precision 18 GHz

SKU: ACC-HL-00075  
 MPN: 101-R045.188

## Description

The Huang Liang SMA Male to SMA Female Radius RA Adapter (Part Number: 101-R045.188) is a high-precision 50 Ω coaxial RF adapter operating up to 18 GHz. Designed with a radius right-angle body, it features free-hanging SMA male and SMA female interfaces, ensuring seamless compatibility. Constructed from 303 stainless steel with a passivated finish, it offers durability and corrosion resistance. The inner contacts are crafted from beryllium copper with gold plating, enhancing signal integrity. The adapter functions efficiently in extreme temperatures ranging from -65 °C to 165 °C. Compliant with ISO 9001 Quality Management and RoHS standards, this adapter meets stringent quality and environmental requirements. Ideal for applications in military, telecommunications, and aerospace industries, Huang Liang leverages over 30 years of RF technology expertise to deliver reliable and high-performance components.



### RF Connector Interface

RF Interface	Body Shape	Mounting
SMA Male	Radius Right Angle	Free Hanging
SMA Female	Radius Right Angle	Free Hanging

## RF Specification

### Huang Liang



Huang Liang is a Taiwanese manufacturer of precision coaxial connectors, adapters and cable assemblies. The company provide solutions to different industries including military, telecommunications, and aerospace.

Over 30 years of experience in developing and designing RF products, Huang Liang has overcome many challenges, resulting in unmatched expertise in the field of RF technology. Huang Liang ...

Start Frequency:	0 GHz	Input Impedance:	50
Stop Frequency:	18 GHz	Inner Contact Resistance:	≤ 6 mΩ
RF Operating Voltage:	≥ 500 Vrms	Insulation Resistance:	≥ 5000 mΩ
		Outer Contact Resistance:	≤ 2 mΩ

VSWR Measurement


Frequency	VSWR	Insertion Loss
18000 MHz	≤ 1.25:1	0.3 dB

# Physical Specification

Body Material:	Stainless Steel (303)	Contact Material:	Beryllium Copper
Body Plating:	Passivated	Contact Plating:	Gold
Insulator Material:	PTFE / Teflon	Min. Operating Temperature:	-65 °C
Weight:	4 g	Max. Operating Temperature:	165 °C
Compliance/Certifications:	ISO 9001 Quality Management	Mating Cycles:	> 500

RoHS

## Drawing



Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

