

Huang Liang SMA Female to SMP Male Adapter

SKU: ACC-HL-00069

MPN: 145-A035.119

Description

The Huang Liang SMA Female to SMP Male Adapter (Part Number: 145-A035.119) is a high-quality 50 Ω coaxial RF adapter. It features a straight-body SMA Female interface and a straight-body SMP Male interface, both designed for free-hanging mounting. This adapter supports SMA Male and SMP Female connections and operates within a frequency range of 0 GHz to 18 GHz.

Constructed from Stainless Steel (303) with a passivated finish, this adapter ensures durability and reliability. The inner contacts are made of Beryllium Copper with gold plating for enhanced connectivity. It performs efficiently in temperatures ranging from -65 °C to 125 °C.

Complying with ISO 9001 Quality Management and RoHS standards, this product guarantees high-quality and environmentally safe performance. Huang Liang, a Taiwanese manufacturer with over 30 years of expertise in RF technology, supplies precision coaxial connectors, adapters, and cable assemblies for various...

[Read More](#)

RF Connector Interface



RF Interface	Body Shape	Mounting
SMA Female	Straight	Free Hanging
SMP Male	Straight	Free Hanging

Huang Liang RF Specification

Huang Liang is a Taiwanese manufacturer of precision coaxial connectors, adapters and cable assemblies. The company provide solutions to different industries including military, telecommunications, and aerospace.

Over 30 years of experience in developing and designing RF products, Huang Liang has overcome many challenges, resulting in unmatched expertise in the field of RF technology. Huang Liang ...

Start Frequency:	0 GHz	Input Impedance:	50
Stop Frequency:	18 GHz	Inner Contact Resistance:	≤ 6 mΩ
RF Operating Voltage:	≥ 335 Vrms	Insulation Resistance:	≥ 5000 mΩ
		Outer Contact Resistance:	≤ 3 mΩ


VSWR Measurement

Frequency	VSWR	Insertion Loss
18000 MHz	≤ 1.4:1	0.4 dB

Physical Specification

Body Material:	Stainless Steel (303)	Contact Material:	Beryllium Copper
Body Plating:	Passivated	Contact Plating:	Gold
Insulator Material:	PTFE / Teflon	Min. Operating Temperature:	-65 °C
Compliance/Certifications:	ISO 9001 Quality Management	Max. Operating Temperature:	125 °C
RoHS		Mating Cycles:	> 500

Drawing



Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

