

Huang Liang BMA Male to SMA Female 2-Hole Flange Mount Adapter

SKU: ACC-HL-00061

MPN: 160-A01F.188

Description

The Huang Liang BMA Male to SMA Female 2-Hole Flange Mount Adapter (Part Number: 160-A01F.188) is a high-quality 50 Ω coaxial RF adapter suitable for various high-frequency applications. It features a BMA Male interface with a straight body and 2-Hole Flange Front Mount, compatible with BMA Female interfaces. The SMA Female interface also has a straight body and 2-Hole Flange Rear Mount, compatible with SMA Male interfaces.

Operating across a frequency range of 0 GHz to 20 GHz, this adapter is constructed from durable 303 stainless steel with a passivated finish, ensuring longevity and resistance to corrosion. The inner contacts are made of beryllium copper with gold plating, enhancing signal integrity and reliable connectivity. The adapter functions effectively within a temperature range of -65 °C to 125 °C, making it suitable for demanding environments.

Manufactured to ISO 9001 Quality Management standards and compliant with RoHS...

[Read More](#)



Huang Liang



Huang Liang is a Taiwanese manufacturer of precision coaxial connectors, adapters and cable assemblies. The company provide solutions to different industries including military, telecommunications, and aerospace.

Over 30 years of experience in developing and designing RF products, Huang Liang has overcome many challenges, resulting in unmatched expertise in the field of RF technology. Huang Liang ...

RF Connector Interface

| RF Interface | Body Shape | Mounting |
|--------------|------------|---------------|
| BMA Male | Straight | 2-Hole Flange |
| SMA Female | Straight | 2-Hole Flange |

RF Specification

| | | | |
|-----------------------|-------------------------|---------------------------|-----------------------------|
| Start Frequency: | 0 GHz | Input Impedance: | 50 |
| Stop Frequency: | 20 GHz | Inner Contact Resistance: | $\leq 6 \text{ m}\Omega$ |
| RF Operating Voltage: | $\geq 375 \text{ Vrms}$ | Insulation Resistance: | $\geq 5000 \text{ m}\Omega$ |
| | | Outer Contact Resistance: | $\leq 2 \text{ m}\Omega$ |


VSWR Measurement

| Frequency | VSWR | Insertion Loss |
|-----------|---------------|----------------|
| 20000 MHz | $\leq 1.25:1$ | 0.27 dB |

Physical Specification

| | | | |
|----------------------------|-----------------------------|-----------------------------|------------------|
| Body Material: | Stainless Steel (303) | Contact Material: | Beryllium Copper |
| Body Plating: | Passivated | Contact Plating: | Gold |
| Insulator Material: | PTFE / Teflon | Min. Operating Temperature: | -65 °C |
| Compliance/Certifications: | ISO 9001 Quality Management | Max. Operating Temperature: | 125 °C |
| RoHS | | Mating Cycles: | > 500 |

Drawing



Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

