

Page



Powertec Wireless Technology  
ABN: 42 082 948 463  
PO Box 1034, Ashmore City  
Queensland, Australia, 4214  
sales@powertec.com.au  
1300 769 378

## **Powertec 4G-5G LPDA Antenna, 698 to 4000 MHz, 4.3-10 Female**

SKU  
IBC-PT-00021  
MPN  
LLP-6940-12.432  
Barcode  
9337692001529


## Description

Powertec's LPDA Antenna is the most popular external antenna solution for poor 4G-5G voice and data service. This single antenna can be used on any mobile network, in any area without worrying about compatibility. It is the ideal roof-mounted antenna for Cel-Fi repeaters.

The LPDA antenna covers all cellular bands between the 700 and 4000 MHz range with a high peak gain which projects maximum energy in the direction of the cell tower, while maintaining a wide enough beam to capture signal reflections off nearby buildings, hills, and signal scattered by trees. Multiband LTE-NR covering major bands between 698 to 4000 MHz.

A Log Periodic Dipole Antenna, or LPDA for short, is a clever antenna design that provides exceptional wideband performance by phasing a series of elements together, much like the Yagi design but with each successive element of a smaller (or larger) length. The result of this clever engineering is an antenna that holds ...

[Read More](#)





## Powertec

Powertec is a wireless technology manufacturer and systems integrator based in Australia. Operating since 1995, Powertec has grown to become the leading wireless technology distributor in its region, and a leading Infratech systems developer. Supporting over 1500 partners the company provides procurement, design, project management, and support services across Australia, New Zealand, Pacific ...

## RF Specification

Start Frequency

698 MHz

Stop Frequency

4000 MHz

Max. Input Power

50 W

Polarisation

[Vertical \(V\)](#)

Input Impedance

50  $\Omega$

RF Connectors

### **Ports RF Interface Body Shape Cable Series Length**

1	<u><a href="#">4.3-10 Female</a></u>	<u><a href="#">Straight</a></u>	<u><a href="#">RG-142</a></u>	300 mm
---	--------------------------------------	---------------------------------	-------------------------------	--------

Frequency Test Data

### **Start Freq. Stop Freq. Peak Gain VSWR Azimuth Elevation F/B Ratio**

698 MHz	803 MHz	11.1 dBi	< 1.8:1	60°	46°	> 28 dB
803 MHz	960 MHz	11.3 dBi	< 1.8:1	60°	47°	> 26 dB
1695 MHz	2200 MHz	11.5 dBi	< 1.8:1	45°	34°	> 24 dB

Start Freq.	Stop Freq.	Peak Gain	VSWR	Azimuth	Elevation	F/B Ratio
2200 MHz	2700 MHz	10.7 dBi	< 1.8:1	50°	40°	> 13 dB
3300 MHz	4000 MHz	9.5 dBi	< 1.6:1	34°	30°	> 9 dB

2200 MHz	2700 MHz	10.7 dBi	< 1.8:1	50°	40°	> 13 dB
3300 MHz	4000 MHz	9.5 dBi	< 1.6:1	34°	30°	> 9 dB

Polar Patterns


Start Frequency

698 MHz


Stop Frequency

960 MHz

**Azimuth Polar Plot**



**Elevation Polar Plot**




Start Frequency

1695 MHz


Stop Frequency

2700 MHz

**Azimuth Polar Plot**



**Elevation Polar Plot**




Start Frequency

3300 MHz


Stop Frequency

4000 MHz

**Azimuth Polar Plot**



**Elevation Polar Plot**



## Physical Specification

Subtype

[Log Periodic Dipole Array](#)

Input Ports

1

MIMO

[1x1 SISO](#)

Min. Operating Temperature

-40 °C

Max. Operating Temperature

65 °C

Dimensions

1240 x 60 x 200

Materials

[Aluminium](#)

Mounting

[Pole Clamp 25 to 52 mm ø](#)

Weight

2.2 kg

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

