Powertec Wireless Technology
ABN: 42 082 948 463
PO Box 1034, Ashmore City
Queensland, Australia, 4214
sales@powertec.com.au
1300 769 378

Huang Liang BMA Female to SMA Female Bulkhead Mount Adapter

SKU
ACC-HL-00063
MPN
160-A615.188

Description

The Huang Liang BMA Female to SMA Female Bulkhead Mount Adapter (Part Number: 160-A615.188) is a high-quality 50 Ω coaxial RF adapter operating in the 0 to 18 GHz frequency range. It features a BMA female interface with a straight body and front bulkhead mount, compatible with BMA male interfaces, and an SMA female interface with a straight body and rear bulkhead mount, compatible with SMA male interfaces.

Constructed from stainless steel (303) with a passivated finish and gold-plated beryllium copper inner contacts, this adapter ensures durability and reliable performance. It operates in temperatures ranging from -65 °C to 125 °C. The product meets ISO 9001 Quality Management standards and is RoHS compliant, ensuring high quality and environmental safety.

Manufactured by Huang Liang, a Taiwanese company with over 30 years of experience in RF technology, this adapter benefits from extensive expertise in precision coaxial connectors...

Read More



Huang Liang
TECHNOLOGIES CO., LTD.

Huang Liang

Huang Liang is a Taiwanese manufacturer of precision coaxial connectors, adapters and cable assemblies. The company provide solutions to different industries including military, telecommunications, and aerospace.

Over 30 years of experience in developing and designing RF products, Huang Liang has overcome many challenges, resulting in unmatched expertise in the field of RF technology. Huang Liang ...

RF Connector Interface

RF Interface	Body Shape	Mounting
BMA Female	Straight	Bulkhead
SMA Female	Straight	Bulkhead

RF Specification


Start Frequency
0 GHz
Stop Frequency
18 GHz
RF Operating Voltage
≥ 375 Vrms
Input Impedance
50 Ω
Inner Contact Resistance
≤ 6 mΩ
Insulation Resistance
≥ 5000 mΩ
Outer Contact Resistance

≤ 2 mΩ
VSWR Measurement

Frequency	VSWR	Insertion Loss
18000 MHz	≤ 1.3:1	0.25 dB

Physical Specification

Body Material
Stainless Steel (303)
Body Plating
Passivated
Insulator Material
PTFE / Teflon
Compliance/Certifications
ISO 9001 Quality Management
,
RoHS
Contact Material
Beryllium Copper
Contact Plating
Gold
Min. Operating Temperature
-65 °C
Max. Operating Temperature
125 °C
Mating Cycles
> 500
Drawing
Image



Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

