

RF Adapter 4.3-10 Female to N Female

SKU

IBC-PT-00001

MPN

AD-432N2

Barcode

9337692001550

Description

The RF Adapter 4.3-10 Female to N Female (Part Number: AD-432N2) is a 50 Ω coaxial adapter from Powertec, designed for high-performance RF applications. It features a 4.3-10 Female interface with a straight body and free hanging mount, compatible with 4.3-10 Male connectors. The opposing N Female interface also has a straight body and free hanging mount, compatible with N Male connectors.

Operating within a frequency range of 0 GHz to 6 GHz, the adapter ensures reliable signal transmission. Constructed from brass with a nickel finish, it has gold-plated brass inner contacts for excellent conductivity. The adapter functions in temperatures ranging from -40 °C to 85 °C, ensuring durability and performance in various environments.

Compliant with ISO 9001 Quality Management and RoHS standards, this adapter guarantees high quality and environmental safety.

Powertec, an Australian wireless technology manufacturer since 1995, is renowned for its...

[Read More](#)



Powertec

Powertec is a wireless technology manufacturer and systems integrator based in Australia. Operating since 1995, Powertec has grown to become the leading wireless technology distributor in its region, and a leading Infratech systems developer. Supporting over 1500 partners the company provides procurement, design, project management, and support services across Australia, New Zealand, Pacific ...

RF Connector Interface

RF Interface Body Shape Mounting

4.3-10 Female	Straight	Free Hanging
N Female	Straight	Free Hanging

RF Specification

Start Frequency

0 GHz

Stop Frequency

6 GHz

RF Operating Voltage

≥ 500 Vrms

Input Impedance

50 Ω

Inner Contact Resistance

≤ 1 m Ω

Insulation Resistance

≥ 5000 m Ω

Outer Contact Resistance

≤ 1 m Ω

VSWR Measurement

Frequency VSWR

6000 MHz $\leq 1.5:1$

Physical Specification

Body Material

[Brass](#)

Body Plating

[Nickel](#)

Insulator Material

[PTFE / Teflon](#)

Compliance/Certifications

[ISO 9001 Quality Management](#)

,

[RoHS](#)

Contact Material

[Brass](#)

Contact Plating

[Gold](#)

Min. Operating Temperature

-40 °C

Max. Operating Temperature

85 °C

Mating Cycles

> 500

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

