

# RF Adapter 4.3-10 Female to N Female

SKU: IBC-PT-00001  
 MPN: AD-432N2  
 Barcode: 9337692001550

## Description

The RF Adapter 4.3-10 Female to N Female (Part Number: AD-432N2) is a 50 Ω coaxial adapter from Powertec, designed for high-performance RF applications. It features a 4.3-10 Female interface with a straight body and free hanging mount, compatible with 4.3-10 Male connectors. The opposing N Female interface also has a straight body and free hanging mount, compatible with N Male connectors.

Operating within a frequency range of 0 GHz to 6 GHz, the adapter ensures reliable signal transmission. Constructed from brass with a nickel finish, it has gold-plated brass inner contacts for excellent conductivity. The adapter functions in temperatures ranging from -40 °C to 85 °C, ensuring durability and performance in various environments.

Compliant with ISO 9001 Quality Management and RoHS standards, this adapter guarantees high quality and environmental safety.


Powertec, an Australian wireless technology manufacturer since 1995, is renowned for its...

[Read More](#)

RF Connector Interface



RF Interface	Body Shape	Mounting
4.3-10 Female	Straight	Free Hanging
N Female	Straight	Free Hanging



**Powertec**

Powertec is a wireless technology manufacturer and systems integrator based in Australia. Operating since 1995, Powertec has grown to become the leading wireless technology distributor in its region, and a leading Infratech systems developer. Supporting over 1500 partners the company provides procurement, design, project management, and support services across Australia, New Zealand, Pacific ...

## RF Specification

Start Frequency:	0 GHz	Input Impedance:	50
Stop Frequency:	6 GHz	Inner Contact Resistance:	$\leq 1 \text{ m}\Omega$
RF Operating Voltage:	$\geq 500 \text{ Vrms}$	Insulation Resistance:	$\geq 5000 \text{ m}\Omega$
		Outer Contact Resistance:	$\leq 1 \text{ m}\Omega$

VSWR Measurement

Frequency	VSWR
6000 MHz	$\leq 1.5:1$

## Physical Specification

Body Material:	Brass	Contact Material:	Brass
Body Plating:	Nickel	Contact Plating:	Gold
Insulator Material:	PTFE / Teflon	Min. Operating Temperature:	-40 °C
Compliance/Certifications:	ISO 9001 Quality Management	Max. Operating Temperature:	85 °C
RoHS	'	Mating Cycles:	> 500

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

