

RF Adapter, N Male to SMA Male

SKU: ACC-PT-00057

MPN: AD-N1SA1

Barcode: 9337692002946

Description

The RF Adapter N Male to SMA Male (Part Number: AD-N1SA1) from Powertec is a high-quality 50 Ω coaxial adapter designed for reliable connectivity. Featuring a straight N Male interface compatible with N Female connectors and a straight SMA Male interface compatible with SMA Female connectors, this adapter supports operating frequencies from 0 GHz to 6 GHz.

Constructed from brass with a gold finish, the adapter's inner contacts are also brass with gold plating, ensuring durability and excellent conductivity. It performs effectively within a temperature range of -55 °C to 155 °C. Compliant with ISO 9001 Quality Management and RoHS standards, this adapter guarantees high-quality performance and safety.

Powertec, based in Australia, has been a leading wireless technology manufacturer and systems integrator since 1995. They specialise in cellular network enhancement, wireless network development, and renewable energy systems, providing...

[Read More](#)



Powertec

Powertec is a wireless technology manufacturer and systems integrator based in Australia. Operating since 1995, Powertec has grown to become the leading wireless technology distributor in its region, and a leading Infratech systems developer. Supporting over 1500 partners the company provides procurement, design, project management, and support services across Australia, New Zealand, Pacific ...

RF Connector Interface

RF Interface	Body Shape	Mounting
N Male	Straight	Free Hanging
SMA Male	Straight	Free Hanging

RF Specification

Start Frequency:	0 GHz	Input Impedance:	50
Stop Frequency:	6 GHz	Inner Contact Resistance:	≤ 1 mΩ
RF Operating Voltage:	≥ 500 Vrms	Insulation Resistance:	≥ 5000 mΩ
		Outer Contact Resistance:	≤ 1 mΩ


VSWR Measurement

Frequency	VSWR
6000 MHz	≤ 1.5:1

Physical Specification

Body Material:	Brass	Contact Material:	Brass
Body Plating:	Gold	Contact Plating:	Gold
Insulator Material:	PTFE / Teflon	Min. Operating Temperature:	-55 °C
Dimensions:	32.9 x 19.8 mm (L x Dia)	Max. Operating Temperature:	155 °C
Weight:	43 g	Mating Cycles:	> 500
Compliance/Certifications:	ISO 9001 Quality Management		
RoHS			

Drawing



Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

