

Page



Powertec Wireless Technology
ABN: 42 082 948 463
PO Box 1034, Ashmore City
Queensland, Australia, 4214
sales@powertec.com.au
1300 769 378

RF Adapter, N Male to SMA Male

SKU
ACC-PT-00057
MPN
AD-N1SA1
Barcode
9337692002946

Description

The RF Adapter N Male to SMA Male (Part Number: AD-N1SA1) from Powertec is a high-quality 50 Ω coaxial adapter designed for reliable connectivity. Featuring a straight N Male interface compatible with N Female connectors and a straight SMA Male interface compatible with SMA Female connectors, this adapter supports operating frequencies from 0 GHz to 6 GHz.

Constructed from brass with a gold finish, the adapter's inner contacts are also brass with gold plating, ensuring durability and excellent conductivity. It performs effectively within a temperature range of -55 °C to 155 °C. Compliant with ISO 9001 Quality Management and RoHS standards, this adapter guarantees high-quality performance and safety.

Powertec, based in Australia, has been a leading wireless technology manufacturer and systems integrator since 1995. They specialise in cellular network enhancement, wireless network development, and renewable energy systems, providing...

[Read More](#)





Powertec

Powertec is a wireless technology manufacturer and systems integrator based in Australia. Operating since 1995, Powertec has grown to become the leading wireless technology distributor in its region, and a leading Infratech systems developer. Supporting over 1500 partners the company provides procurement, design, project management, and support services across Australia, New Zealand, Pacific ...

RF Connector Interface

RF Interface Body Shape Mounting

N Male	Straight	Free Hanging
SMA Male	Straight	Free Hanging

RF Specification

Start Frequency

0 GHz

Stop Frequency

6 GHz

RF Operating Voltage

≥ 500 Vrms

Input Impedance

50 Ω

Inner Contact Resistance

≤ 1 m Ω

Insulation Resistance

≥ 5000 m Ω

Outer Contact Resistance

$\leq 1 \text{ m}\Omega$

VSWR Measurement

Frequency VSWR

6000 MHz $\leq 1.5:1$

Physical Specification

Body Material

[Brass](#)

Body Plating

[Gold](#)

Insulator Material

[PTFE / Teflon](#)

Dimensions

32.9 x 19.8 mm (L x Dia)

Weight

43 g

Compliance/Certifications

[ISO 9001 Quality Management](#)

,

[RoHS](#)

Contact Material

[Brass](#)

Contact Plating

[Gold](#)

Min. Operating Temperature

-55 °C

Max. Operating Temperature


155 °C

Mating Cycles

> 500

Drawing

Image



Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

