

RF Adapter, N Male to SMA Female

SKU: ACC-PT-00054

MPN: AD-N1SA2

Barcode: 9337692001475

Description

The RF Adapter N Male to SMA Female (Part Number: AD-N1SA2) by Powertec is a high-quality 50 Ω coaxial adapter designed for reliable connectivity. It features an N Male interface and an SMA Female interface, both with straight bodies and free-hanging mounting mechanisms, ensuring compatibility with N Female and SMA Male connectors, respectively.

This adapter supports an operating frequency range from 0 GHz to 6 GHz, making it versatile for various applications. Constructed from brass with a gold finish, it ensures durability and optimal conductivity. The inner contacts are also brass with gold plating, enhancing signal integrity. It performs efficiently in temperatures ranging from -55 °C to 155 °C and complies with ISO 9001 Quality Management and RoHS standards, ensuring high manufacturing quality and environmental safety.

Ideal for applications in wireless technology and network enhancement, this adapter is a reliable component for...

[Read More](#)



Powertec

Powertec is a wireless technology manufacturer and systems integrator based in Australia. Operating since 1995, Powertec has grown to become the leading wireless technology distributor in its region, and a leading Infratech systems developer. Supporting over 1500 partners the company provides procurement, design, project management, and support services across Australia, New Zealand, Pacific ...

RF Connector Interface

RF Interface	Body Shape	Mounting
N Male	Straight	Free Hanging
SMA Female	Straight	Free Hanging

RF Specification

Start Frequency:	0 GHz	Input Impedance:	50
Stop Frequency:	6 GHz	Inner Contact Resistance:	$\leq 1 \text{ m}\Omega$
RF Operating Voltage:	$\geq 500 \text{ Vrms}$	Insulation Resistance:	$\geq 5000 \text{ m}\Omega$
		Outer Contact Resistance:	$\leq 1 \text{ m}\Omega$


VSWR Measurement

Frequency	VSWR
6000 MHz	$\leq 1.5:1$

Physical Specification

Body Material:	Brass	Contact Material:	Brass
Body Plating:	Gold	Contact Plating:	Gold
Insulator Material:	PTFE / Teflon	Min. Operating Temperature:	-55 °C
Dimensions:	32.7 x 19.8 mm (L x Dia)	Max. Operating Temperature:	155 °C
Compliance/Certifications:	ISO 9001 Quality Management	Mating Cycles:	> 500
RoHS			

Drawing



Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

