

RF Adapter, N Female to SMA Male

SKU: ACC-PT-00036
 MPN: AD-N2SA1
 Barcode: 9337692001468

Description

The RF Adapter N Female to SMA Male (Part Number: AD-N2SA1) by Powertec is a high-quality, 50 Ω coaxial adapter designed for seamless connectivity between N Male and SMA Female interfaces. This adapter supports a frequency range of 0 GHz to 6 GHz, ensuring broad compatibility for various RF applications. It features a straight body shape with a free-hanging mounting mechanism, facilitating straightforward integration into your setup.

Constructed from brass with a gold and nickel finish, the adapter guarantees durability and excellent performance. The inner contacts are made of brass, plated with gold for enhanced conductivity. It operates efficiently within a temperature range of -55 °C to 155 °C, making it suitable for diverse environmental conditions.


Manufactured to meet ISO 9001 quality standards and RoHS compliance, this adapter exemplifies reliability and adherence to international quality benchmarks. Powertec, a leading wireless...

[Read More](#)

RF Connector Interface



RF Interface	Body Shape	Mounting
N Female	Straight	Free Hanging
SMA Male	Straight	Free Hanging



RF Specification

Powertec

Powertec is a wireless technology manufacturer and systems integrator based in Australia. Operating since 1995, Powertec has grown to become the leading wireless technology distributor in its region, and a leading Infratech systems developer. Supporting over 1500 partners the company provides procurement, design, project management, and support services across Australia, New Zealand, Pacific ...

Start Frequency:	0 GHz	Input Impedance:	50
Stop Frequency:	6 GHz	Inner Contact Resistance:	$\leq 1 \text{ m}\Omega$
RF Operating Voltage:	$\geq 500 \text{ Vrms}$	Insulation Resistance:	$\geq 5000 \text{ m}\Omega$
		Outer Contact Resistance:	$\leq 1 \text{ m}\Omega$

VSWR Measurement


Frequency	VSWR
6000 MHz	$\leq 1.5:1$

Physical Specification

Body Material:	Brass	Contact Material:	Brass
Body Plating:	Gold, Nickel	Contact Plating:	Gold
Insulator Material:	PTFE / Teflon	Min. Operating Temperature:	$-55 \text{ }^\circ\text{C}$
Dimensions:	33.5 x 15.9 mm (L x Dia)	Max. Operating Temperature:	$155 \text{ }^\circ\text{C}$
Weight:	45 g	Mating Cycles:	> 500
Compliance/Certifications:	ISO 9001 Quality Management		

RoHS

Drawing



Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

