

RF Adapter, N Female to SMA Female

SKU: ACC-PT-00318

MPN: AD-N2SA2

Barcode: 9337692002939

Description

The RF Adapter N Female to SMA Female (Part Number: AD-N2SA2) from Powertec is a 50 Ω coaxial adapter designed for versatile RF applications. It features a N Female interface and a SMA Female interface, both with straight body shapes and free-hanging mounting mechanisms, compatible with N Male and SMA Male interfaces respectively.

This adapter operates within a frequency range of 0 GHz to 6 GHz, making it suitable for various high-frequency applications. Constructed from brass with a nickel finish, it ensures durability and reliable performance. The inner contacts are crafted from brass with gold plating, providing excellent conductivity and corrosion resistance.

It functions efficiently in temperature conditions ranging from -55 $^{\circ}$ C to 155 $^{\circ}$ C. The adapter complies with ISO 9001 Quality Management standards and RoHS regulations, ensuring high quality and environmental safety.

Powertec, established in 1995 and based in Australia, is a leader...

[Read More](#)



Powertec

Powertec is a wireless technology manufacturer and systems integrator based in Australia. Operating since 1995, Powertec has grown to become the leading wireless technology distributor in its region, and a leading Infratech systems developer. Supporting over 1500 partners the company provides procurement, design, project management, and support services across Australia, New Zealand, Pacific ...

RF Connector Interface

RF Interface	Body Shape	Mounting
N Female	Straight	Free Hanging
SMA Female	Straight	Free Hanging

RF Specification

Start Frequency:	0 GHz	Input Impedance:	50
Stop Frequency:	6 GHz	Inner Contact Resistance:	$\leq 1 \text{ m}\Omega$
RF Operating Voltage:	$\geq 500 \text{ Vrms}$	Insulation Resistance:	$\geq 5000 \text{ m}\Omega$
		Outer Contact Resistance:	$\leq 1 \text{ m}\Omega$


VSWR Measurement

Frequency	VSWR
6000 MHz	$\leq 1.5:1$

Physical Specification

Body Material:	Brass	Contact Material:	Brass
Body Plating:	Gold, Nickel	Contact Plating:	Gold
Insulator Material:	PTFE / Teflon	Min. Operating Temperature:	-55 °C
Dimensions:	33.2 x 15.9 mm (L x Dia)	Max. Operating Temperature:	155 °C
Weight:	40 g	Mating Cycles:	> 500
Compliance/Certifications:	ISO 9001 Quality Management		
RoHS			

Drawing



Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

