

Page



Powertec Wireless Technology
ABN: 42 082 948 463
PO Box 1034, Ashmore City
Queensland, Australia, 4214
sales@powertec.com.au
1300 769 378

RF Adapter RP-SMA Female to SMA Male

SKU
ACC-PT-00333
MPN
AD-RPSA2SA1
Barcode
9337692003622

Description

The RF Adapter RP-SMA Female to SMA Male (Part Number: AD-RSA2SA1) by Powertec is a high-quality 50 Ω coaxial RF adapter. It features a RP-SMA Female connector with a straight, free-hanging body, compatible with RP-SMA Male interfaces, and a SMA Male connector with a straight, free-hanging body, compatible with SMA Female interfaces. The adapter supports an operating frequency range from 0 GHz to 6 GHz.

Constructed from Brass with a Gold finish, the adapter ensures robust performance and longevity. The inner contacts are also Brass with Gold plating, providing excellent conductivity and signal integrity. It operates within a temperature range of -55 °C to 155 °C, making it suitable for a wide range of environments.

This adapter meets ISO 9001 Quality Management and RoHS compliance standards, ensuring reliable quality and adherence to safety regulations. Powertec, an established Australian manufacturer since 1995, specialises in wireless...

[Read More](#)





Powertec

Powertec is a wireless technology manufacturer and systems integrator based in Australia. Operating since 1995, Powertec has grown to become the leading wireless technology distributor in its region, and a leading Infratech systems developer. Supporting over 1500 partners the company provides procurement, design, project management, and support services across Australia, New Zealand, Pacific ...

RF Connector Interface

RF Interface Body Shape Mounting

RP-SMA Female	Straight	Free Hanging
SMA Male	Straight	Free Hanging

RF Specification

Start Frequency

0 GHz

Stop Frequency

6 GHz

RF Operating Voltage

≥ 500 Vrms

Input Impedance

50 Ω

Inner Contact Resistance

≤ 1 m Ω

Insulation Resistance

≥ 5000 m Ω

Outer Contact Resistance

$\leq 1 \text{ m}\Omega$

VSWR Measurement

Frequency VSWR

6000 MHz $\leq 1.5:1$

Physical Specification

Body Material

[Brass](#)

Body Plating

[Gold](#)

Insulator Material

[PTFE / Teflon](#)

Dimensions

17 x 8 mm (L x Dia)

Weight

5 g

Compliance/Certifications

[ISO 9001 Quality Management](#)

,

[RoHS](#)

Contact Material

[Brass](#)

Contact Plating

[Gold](#)

Min. Operating Temperature

-55 °C

Max. Operating Temperature


155 °C

Mating Cycles

> 500

Drawing

Image



Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

