

Page



Powertec Wireless Technology
ABN: 42 082 948 463
PO Box 1034, Ashmore City
Queensland, Australia, 4214
sales@powertec.com.au
1300 769 378

RF Adapter, TNC-RP Male to RP-SMA Male

SKU
ACC-PT-00491
MPN
AD-TNRP1SARP1
Barcode
9337692005138

Description

The RF Adapter RP-TNC Male to RP-SMA Male (Part Number: AD-RTN1RSA1) by Powertec is a 50 Ω coaxial adapter designed for high-quality RF connections. It features an RP-TNC Male interface and an RP-SMA Male interface, both with a straight body shape and free-hanging mounting mechanism. This adapter is compatible with RP-TNC Female and RP-SMA Female interfaces, respectively, and operates efficiently within a frequency range of 0 GHz to 6 GHz.

Constructed from Brass with a Nickel finish, the adapter's inner contacts are Gold-plated Brass for enhanced conductivity and durability. It is built to withstand extreme temperatures, operating between -55 °C and 155 °C.

Manufactured to meet ISO 9001 Quality Management standards and RoHS compliance, this adapter ensures reliable performance and adherence to environmental regulations.

Powertec, an Australian company established in 1995, specialises in wireless technology and systems integration. They are...

[Read More](#)





Powertec

Powertec is a wireless technology manufacturer and systems integrator based in Australia. Operating since 1995, Powertec has grown to become the leading wireless technology distributor in its region, and a leading Infratech systems developer. Supporting over 1500 partners the company provides procurement, design, project management, and support services across Australia, New Zealand, Pacific ...

RF Connector Interface

RF Interface Body Shape Mounting

[RP-TNC Male](#) [Straight](#) [Free Hanging](#)

[RP-SMA Male](#) [Straight](#) [Free Hanging](#)

RF Specification

Start Frequency

0 GHz

Stop Frequency

6 GHz

RF Operating Voltage

≥ 500 Vrms

Input Impedance

50 Ω

Inner Contact Resistance

≤ 1 m Ω

Insulation Resistance

≥ 5000 m Ω

Outer Contact Resistance

≤ 1 mΩ

VSWR Measurement

Frequency VSWR

6000 MHz ≤ 1.5:1

Physical Specification

Body Material

[Brass](#)

Body Plating

[Nickel](#)

Insulator Material

[PTFE / Teflon](#)

Compliance/Certifications

[ISO 9001 Quality Management](#)

,

[RoHS](#)

Contact Material

[Brass](#)

Contact Plating

[Gold](#)

Min. Operating Temperature

-55 °C

Max. Operating Temperature

155 °C

Mating Cycles

> 500

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

