

RF Adapter, SMA Male to TNC Female

SKU: ACC-PT-00091
 MPN: AD-SA1TN2
 Barcode: 9337692002953

Description

The RF Adapter SMA Male to TNC Female (Part Number: AD-SA1TN2) by Powertec is a 50 Ω coaxial adapter designed for high-frequency applications. It features a SMA Male to TNC Female interface, both with straight body shapes and free-hanging mounting mechanisms, compatible with their respective connectors.

This adapter supports an operating frequency range from 0 GHz to 6 GHz, making it suitable for a wide variety of RF applications. Constructed from Brass with a Gold finish and inner contacts made of Phosphor Bronze with Gold plating, it ensures high durability and reliable performance. It operates efficiently in extreme temperatures ranging from -65 °C to 165 °C.

Manufactured to ISO 9001 Quality Management standards and compliant with RoHS, this adapter guarantees high quality and environmental safety.


Powertec, an Australian-based wireless technology manufacturer and systems integrator, has been a leader in the industry since 1995. The...

[Read More](#)

RF Connector Interface



RF Interface	Body Shape	Mounting
SMA Male	Straight	Free Hanging
TNC Female	Straight	Free Hanging



Powertec

Powertec is a wireless technology manufacturer and systems integrator based in Australia. Operating since 1995, Powertec has grown to become the leading wireless technology distributor in its region, and a leading Infratech systems developer. Supporting over 1500 partners the company provides procurement, design, project management, and support services across Australia, New Zealand, Pacific ...

RF Specification

Start Frequency:	0 GHz	Input Impedance:	50
Stop Frequency:	6 GHz	Inner Contact Resistance:	$\leq 1 \text{ m}\Omega$
RF Operating Voltage:	$\geq 500 \text{ Vrms}$	Insulation Resistance:	$\geq 5000 \text{ m}\Omega$
		Outer Contact Resistance:	$\leq 1 \text{ m}\Omega$

VSWR Measurement


Frequency	VSWR
6000 MHz	$\leq 1.25:1$

Physical Specification

Body Material:	Brass	Contact Material:	Phosphor Bronze
Body Plating:	Gold	Contact Plating:	Gold
Insulator Material:	PTFE / Teflon	Min. Operating Temperature:	-65 °C
Dimensions:	28.5 x 12 mm (L x Dia)	Max. Operating Temperature:	165 °C
Compliance/Certifications:	ISO 9001 Quality Management	Mating Cycles:	> 500

RoHS

Drawing



Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

