Powertec Wireless Technology
ABN: 42 082 948 463
PO Box 1034, Ashmore City
Queensland, Australia, 4214
sales@powertec.com.au
1300 769 378

RF Adapter SMA Female to SMA Female, Bulkhead Rear Mount

SKU
ACC-PT-00163
MPN
AD-SA2SA2-BRM
Barcode
9337692001543

Description

The RF Adapter SMA Female to SMA Female, Bulkhead Rear Mount (Part Number: AD-SA2SA2-BRM) by Powertec is a high-quality 50 Ω coaxial adapter designed for seamless RF connections. Featuring dual SMA Female interfaces with straight body shapes, this adapter supports mounting mechanisms for both bulkhead front and rear. It ensures compatibility with SMA Male interfaces.

Operating within a frequency range of 0 GHz to 6 GHz, this adapter is built from durable Brass with a Gold finish, and includes brass inner contacts with gold plating for reliable performance. It functions efficiently in temperatures ranging from -55 °C to 155 °C. Compliant with ISO 9001 Quality Management and RoHS standards, this product guarantees exceptional quality.

Powertec, an Australian wireless technology manufacturer and systems integrator, has been a leader since 1995. Known for enhancing cellular networks and developing wireless and renewable energy systems...

Read More



Powertec

Powertec is a wireless technology manufacturer and systems integrator based in Australia. Operating since 1995, Powertec has grown to become the leading wireless technology distributor in its region, and a leading Infratech systems developer. Supporting over 1500 partners the company provides procurement, design, project management, and support services across Australia, New Zealand, Pacific ...

RF Connector Interface

RF Interface	Body Shape	Mounting
SMA Female	Straight	Bulkhead
SMA Female	Straight	Bulkhead

RF Specification


Start Frequency
0 GHz
Stop Frequency
6 GHz
RF Operating Voltage
≥ 500 Vrms
Input Impedance
50 Ω
Inner Contact Resistance
≤ 1 mΩ
Insulation Resistance
≥ 5000 mΩ
Outer Contact Resistance
≤ 1 mΩ

VSWR Measurement

Frequency	VSWR
6000 MHz	≤ 1.3:1

Physical Specification

Body Material
Brass
Body Plating
Gold
Insulator Material
PTFE / Teflon
Dimensions
22.1 x 11 mm (L x Dia)
Weight
5.8 g
Compliance/Certifications
ISO 9001 Quality Management
,
RoHS
Contact Material
Brass
Contact Plating
Gold
Min. Operating Temperature
-55 °C
Max. Operating Temperature
155 °C
Mating Cycles
> 500
Drawing
Image



Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

