Powertec Wireless Technology
ABN: 42 082 948 463
PO Box 1034, Ashmore City
Queensland, Australia, 4214
sales@powertec.com.au
1300 769 378

RF Adapter SMA Female to SMA Female Right Angle

SKU
ACC-PT-00335
MPN
AD-SA2SA2.RA
Barcode
9337692003639

Description

The RF Adapter SMA Female to SMA Female Right Angle (Part Number: AD-SA2SA2-RA) by Powertec is a 50 Ω coaxial adapter. It features two SMA Female interfaces with right-angle body shapes and free hanging mounting mechanisms, compatible with SMA Male interfaces. Designed to operate in the frequency range of 0 GHz to 6 GHz, this adapter is built with brass body and contacts, and gold finish.

This adapter can function in temperatures ranging from -55 °C to 125 °C, ensuring reliable performance in varied environments. It adheres to ISO 9001 Quality Management standards and is RoHS compliant, guaranteeing high quality and environmental safety.

Powertec, an Australian wireless technology manufacturer, has been a leader in the industry since 1995, providing advanced solutions in cellular network enhancement, wireless network development, and renewable energy systems.



Powertec

Powertec is a wireless technology manufacturer and systems integrator based in Australia. Operating since 1995, Powertec has grown to become the leading wireless technology distributor in its region, and a leading Infratech systems developer. Supporting over 1500 partners the company provides procurement, design, project management, and support services across Australia, New Zealand, Pacific ...

RF Connector Interface

RF Interface	Body Shape	Mounting
SMA Female	Right Angle	Free Hanging
SMA Female	Right Angle	Free Hanging

RF Specification


Start Frequency
0 GHz
Stop Frequency
6 GHz
RF Operating Voltage
≥ 500 Vrms
Input Impedance
50 Ω
Inner Contact Resistance
≤ 1 mΩ
Insulation Resistance
≥ 5000 mΩ
Outer Contact Resistance
≤ 1 mΩ

VSWR Measurement

Frequency	VSWR
6000 MHz	≤ 1.5:1

Physical Specification

Body Material
Brass
Body Plating
Gold
Insulator Material
PTFE / Teflon
Dimensions
14 x 14 x 7 mm
Weight
4 g
Compliance/Certifications
ISO 9001 Quality Management
,
RoHS
Contact Material
Brass
Contact Plating
Gold
Min. Operating Temperature
-55 °C
Max. Operating Temperature
125 °C
Mating Cycles
> 500
Drawing
Image



Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

