

Powertec Wireless Technology ABN: 42 082 948 463 PO Box 1034, Ashmore City Queensland, Australia, 4214 sales@powertec.com.au 1300 769 378

# Huang Liang 3.5 mm Female to N Female Adapter

SKU: ACC-HL-00059 MPN: ADU1-35F1-NF1

### Description

The Huang Liang 3.5 mm Female to N Female Adapter (Part Number: ADU1-35F1-NF1) is a high-quality 50  $\Omega$  coaxial RF adapter. It features a 3.5 mm Female interface compatible with 3.5 mm Male and SMA Male connections, and an N Female interface compatible with N Male connections. Both interfaces have a straight body and free-hanging mounting mechanism.

This adapter operates across a frequency range of 0 GHz to 18 GHz, making it versatile for various RF applications. Constructed from passivated stainless steel (303) and featuring gold-plated beryllium copper inner contacts, it ensures durability and exceptional performance. It is suitable for use in environments ranging from -40 °C to 105 °C.

Manufactured to ISO 9001 quality standards and RoHS compliant, this adapter is ideal for applications in military, telecommunications, and aerospace industries. With over 30 years of expertise in RF technology, Huang Liang delivers reliable and precise RF...

Read More





#### **Huang Liang**

Huang Liang is a Taiwanese manufacturer of precision coaxial connectors, adapters and cable assemblies. The company provide solutions to different industries including military, telecommunications, and aerospace.

Over 30 years of experience in developing and designing RF products, Huang Liang has overcome many challenges, resulting in unmatched expertise in the field of RF technology. Huang Liang ...

## RF Connector Interface

RF Interface	Body Shape	Mounting
3.5 mm Female	Straight	Free Hanging
N Female	Straight	Free Hanging

## **RF** Specification


Start Frequency:	0 GHz	Input Impedance:	50
Stop Frequency:	18 GHz	Inner Contact Resistance:	≤ 6 mΩ
RF Operating Voltage:	≥ 250 Vrms	Insulation Resistance:	≥ 3000 mΩ
		Outer Contact Resistance:	≤ 2 mΩ

### **VSWR** Measurement

Frequency	VSWR	Insertion Loss
18000 MHz	≤ 1.2:1	0.25 dB

# **Physical Specification**

Stainless Steel (303)	Contact Material:	Beryllium Copper
Passivated	Contact Plating:	Gold
PTFE / Teflon	Min. Operating Temperature:	-40 °C
28.6 g	Max. Operating Temperature:	105 °C
ISO 9001 Quality Management	Mating Cycles:	> 500
,		
	Passivated  PTFE / Teflon  28.6 g	Passivated Contact Plating:  PTFE / Teflon Min. Operating Temperature:  28.6 g Max. Operating Temperature:



Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

