

Huang Liang 2.92 mm Female to 2.92 mm Female Adapter

SKU: ACC-HL-00043
 MPN: ADU1-KF1-KF1

Description

The Huang Liang 2.92 mm Female to 2.92 mm Female Adapter (Part Number: ADU1-KF1-KF1) is a high-quality, 50 Ω coaxial RF adapter. Designed for compatibility with 2.92 mm Male interfaces, it features a straight body shape and a free-hanging mounting mechanism. This adapter operates across a broad frequency range from 0 GHz to 40 GHz, making it versatile for various applications.

Constructed from 303 stainless steel with a passivated finish, the adapter ensures durability and corrosion resistance. The inner contacts are made of beryllium copper with gold plating, offering excellent conductivity and performance reliability. It is operational within a temperature range of -65 °C to 150 °C, ensuring stability in diverse environmental conditions.

Huang Liang, a reputable Taiwanese manufacturer, guarantees top-notch quality and compliance with ISO 9001 and RoHS standards. With over 30 years of experience in RF technology, Huang Liang provides...

[Read More](#)

RF Connector Interface



RF Interface	Body Shape	Mounting
2.92 mm Female	Straight	Free Hanging
2.92 mm Female	Straight	Free Hanging

Huang Liang



RF Specification

Huang Liang is a Taiwanese manufacturer of precision coaxial connectors, adapters and cable assemblies. The company provide solutions to different industries including military, telecommunications, and aerospace.

Over 30 years of experience in developing and designing RF products, Huang Liang has overcome many challenges, resulting in unmatched expertise in the field of RF technology. Huang Liang...

Start Frequency:	0 GHz	Input Impedance:	50
Stop Frequency:	40 GHz	Inner Contact Resistance:	$\leq 3 \text{ m}\Omega$
RF Operating Voltage:	$\geq 350 \text{ Vrms}$	Insulation Resistance:	$\geq 5000 \text{ m}\Omega$
		Outer Contact Resistance:	$\leq 2 \text{ m}\Omega$


VSWR Measurement

Frequency	VSWR	Insertion Loss
40000 MHz	$\leq 1.2:1$	0.25 dB

Physical Specification

Body Material:	Stainless Steel (303)	Contact Material:	Beryllium Copper
Body Plating:	Passivated	Contact Plating:	Gold
Insulator Material:	PTFE / Teflon	Min. Operating Temperature:	$-65 \text{ }^\circ\text{C}$
Compliance/Certifications:	ISO 9001 Quality Management	Max. Operating Temperature:	$150 \text{ }^\circ\text{C}$
RoHS		Mating Cycles:	> 500

Drawing



Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

