

Huang Liang 2.92 mm Male to N Female Adapter

SKU

ACC-HL-00047

MPN

ADU1-KM1-NF1

Description

The Huang Liang 2.92 mm Male to N Female Adapter (Part Number: ADU1-KM1-NF1) is a high-quality 50 Ω coaxial RF adapter designed for versatile applications. It features a 2.92 mm Male interface and an N Female interface, both with a straight body and free-hanging mounting mechanism. This adapter supports frequencies from 0 GHz to 18 GHz, making it suitable for a wide range of RF applications.

Constructed from stainless steel (303) with a passivated finish, the adapter ensures durability and excellent performance. The inner contacts are made of beryllium copper with gold plating, providing reliable conductivity. It operates efficiently in temperatures ranging from -65 °C to 150 °C, making it suitable for various environments.

This product complies with ISO 9001 Quality Management standards and RoHS regulations, ensuring high-quality and environmentally friendly manufacturing. Huang Liang, a Taiwanese manufacturer with over 30 years of...

[Read More](#)



[Huang Liang](#)

Huang Liang is a Taiwanese manufacturer of precision coaxial connectors, adapters and cable assemblies. The company provide solutions to different industries including military, telecommunications, and aerospace.

Over 30 years of experience in developing and designing RF products, Huang Liang has overcome many challenges, resulting in unmatched expertise in the field of RF technology. Huang Liang ...

RF Connector Interface

RF Interface Body Shape Mounting

2.92 mm Male	Straight	Free Hanging
N Female	Straight	Free Hanging

RF Specification

Start Frequency

0 GHz

Stop Frequency

18 GHz

RF Operating Voltage

≥ 350 Vrms

Input Impedance

50 Ω

Inner Contact Resistance

≤ 3 m Ω

Insulation Resistance

≥ 5000 m Ω

Outer Contact Resistance

≤ 2 m Ω

VSWR Measurement

Frequency VSWR Insertion Loss

18000 MHz $\leq 1.2:1$ 0.25 dB

Physical Specification

Body Material

[Stainless Steel \(303\)](#)

Body Plating

[Passivated](#)

Insulator Material

[PTFE / Teflon](#)

Compliance/Certifications

[ISO 9001 Quality Management](#)

,

[RoHS](#)

Contact Material

[Beryllium Copper](#)

Contact Plating

[Gold](#)

Min. Operating Temperature

-65 °C

Max. Operating Temperature


150 °C

Mating Cycles

> 500

Drawing

Image



Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

