Powertec Wireless Technology
ABN: 42 082 948 463
PO Box 1034, Ashmore City
Queensland, Australia, 4214
sales@powertec.com.au
1300 769 378

Huang Liang 2.4 mm Female to SMA Female Adapter

SKU
ACC-HL-00030
MPN
ADU1-QF1-SMF1

Description

The Huang Liang 2.4 mm Female to SMA Female Adapter (Part Number: ADU1-QF1-SMF1) is a high-quality 50 Ω coaxial RF adapter designed for seamless connectivity between 2.4 mm and SMA interfaces. This adapter features a straight body with a free-hanging mounting mechanism, making it compatible with 2.4 mm Male, 1.85 mm Male, and SMA Male connectors. It supports an operating frequency range from 0 GHz to 26.5 GHz.

Constructed from Stainless Steel (303) with a passivated finish, the adapter ensures durability and corrosion resistance. The inner contacts are made of Beryllium Copper with gold plating, offering excellent conductivity and signal integrity. It operates effectively within a temperature range of -65 °C to 150 °C.

The adapter complies with ISO 9001 Quality Management standards and is RoHS compliant, ensuring reliability and environmental safety. Huang Liang, a Taiwanese manufacturer with over 30 years of expertise in RF technology...

Read More



Huang Liang

Huang Liang is a Taiwanese manufacturer of precision coaxial connectors, adapters and cable assemblies. The company provide solutions to different industries including military, telecommunications, and aerospace.

Over 30 years of experience in developing and designing RF products, Huang Liang has overcome many challenges, resulting in unmatched expertise in the field of RF technology. Huang Liang ...

RF Connector Interface

RF Interface	Body Shape	Mounting
2.4 mm Female	Straight	Free Hanging
SMA Female	Straight	Free Hanging

RF Specification


Start Frequency
0 GHz
Stop Frequency
26.5 GHz
RF Operating Voltage
≥ 350 Vrms
Input Impedance
50 Ω
Inner Contact Resistance
≤ 6 mΩ
Insulation Resistance
≥ 5000 mΩ
Outer Contact Resistance

≤ 2 mΩ
VSWR Measurement

Frequency	VSWR	Insertion Loss
26500 MHz	≤ 1.2:1	0.25 dB

Physical Specification

Body Material
Stainless Steel (303)
Body Plating
Passivated
Insulator Material
PTFE / Teflon
Compliance/Certifications
ISO 9001 Quality Management
,
RoHS
Contact Material
Beryllium Copper
Contact Plating
Gold
Min. Operating Temperature
-65 °C
Max. Operating Temperature
150 °C
Mating Cycles
> 500
Drawing
Image



Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

