

Huang Liang 2.4 mm Male to 3.5 mm Male Adapter

SKU: ACC-HL-00025

MPN: ADU1-QM1-35M1

Description

The Huang Liang 2.4 mm Male to 3.5 mm Male Adapter (Part Number: ADU1-QM1-35M1) is a 50 Ω coaxial RF adapter designed for high-performance applications. Manufactured in Taiwan, this adapter features a 2.4 mm Male interface with a straight, free-hanging body compatible with 2.4 mm Male and 1.85 mm Female connectors. The 3.5 mm Male interface, also with a straight, free-hanging body, is compatible with 3.5 mm Female and SMA Female connectors.

Operating within a frequency range of 0 GHz to 34 GHz, the adapter ensures reliable performance across a wide spectrum. Constructed from 303 Stainless Steel with a passivated finish, it boasts durability and resistance to corrosion. The inner contacts are made of Beryllium Copper with Gold plating, ensuring excellent conductivity and signal integrity. The adapter functions effectively in temperatures ranging from -40 °C to 105 °C.

Complying with ISO 9001 Quality Management and RoHS standards, this...

[Read More](#)



Huang Liang



Huang Liang is a Taiwanese manufacturer of precision coaxial connectors, adapters and cable assemblies. The company provide solutions to different industries including military, telecommunications, and aerospace.

Over 30 years of experience in developing and designing RF products, Huang Liang has overcome many challenges, resulting in unmatched expertise in the field of RF technology. Huang Liang ...

RF Connector Interface

RF Interface	Body Shape	Mounting
2.4 mm Male	Straight	Free Hanging
3.5 mm Male	Straight	Free Hanging

RF Specification

Start Frequency:	0 GHz	Input Impedance:	50
Stop Frequency:	34 GHz	Inner Contact Resistance:	≤ 6 mΩ
RF Operating Voltage:	≥ 250 Vrms	Insulation Resistance:	≥ 3000 mΩ
		Outer Contact Resistance:	≤ 2 mΩ


VSWR Measurement

Frequency	VSWR	Insertion Loss
34000 MHz	≤ 1.2:1	0.35 dB

Physical Specification

Body Material:	Stainless Steel (303)	Contact Material:	Beryllium Copper
Body Plating:	Passivated	Contact Plating:	Gold
Insulator Material:	PTFE / Teflon	Min. Operating Temperature:	-40 °C
Weight:	6.8 g	Max. Operating Temperature:	105 °C
Compliance/Certifications:	ISO 9001 Quality Management	Mating Cycles:	> 500
RoHS			

Drawing



Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

