

Powertec Wireless Technology ABN: 42 082 948 463 PO Box 1034, Ashmore City Queensland, Australia, 4214 sales@powertec.com.au 1300 769 378

## Huang Liang 2.4 mm Male to 2.92 mm Male Adapter

SKU: ACC-HL-00027 MPN: ADU1-QM1-KM1

### Description

The Huang Liang 2.4 mm Male to 2.92 mm Male Adapter (Part Number: ADU1-QM1-KM1) is a high-quality 50  $\Omega$  coaxial RF adapter. It features 2.4 mm Male and 2.92 mm Male interfaces, both with a straight body shape and free-hanging mounting mechanism. The adapter supports a frequency range from 0 GHz to 40 GHz, making it suitable for a wide range of RF applications.

Constructed from stainless steel (303) with a passivated finish, the adapter ensures durability and corrosion resistance. The inner contacts are made of beryllium copper with gold plating, offering excellent conductivity and signal integrity. It is designed to operate in extreme temperatures, from -65 °C to 150 °C, ensuring reliability in various environments.

The adapter complies with ISO 9001 Quality Management standards and is RoHS compliant, underscoring its commitment to quality and environmental standards. With over 30 years of experience, Huang Liang is a trusted Taiwanese...

Read More



#### **Huang Liang**



Huang Liang is a Taiwanese manufacturer of precision coaxial connectors, adapters and cable assemblies. The company provide solutions to different industries including military, telecommunications, and aerospace.

Over 30 years of experience in developing and designing RF products, Huang Liang has overcome many challenges, resulting in unmatched expertise in the field of RF technology. Huang Liang ...

## RF Connector Interface

RF Interface	Body Shape	Mounting
2.4 mm Male	Straight	Free Hanging
2.92 mm Male	Straight	Free Hanging

## **RF** Specification


Start Frequency:	0 GHz	Input Impedance:	50
Stop Frequency:	40 GHz	Inner Contact Resistance:	≤ 3 mΩ
RF Operating Voltage:	≥ 350 Vrms	Insulation Resistance:	≥ 5000 mΩ
		Outer Contact Resistance:	≤ 2 mΩ

### **VSWR** Measurement

Frequency	VSWR	Insertion Loss
40000 MHz	≤ 1.2:1	0.25 dB

# **Physical Specification**

Body Material:	Stainless Steel (303)	Contact Material:	Beryllium Copper
Body Plating:	Passivated	Contact Plating:	Gold
Insulator Material:	PTFE / Teflon	Min. Operating Temperature:	-65 °C
Compliance/Certifications:	ISO 9001 Quality Management	Max. Operating Temperature:	150 °C
RoHS	1	Mating Cycles:	> 500



Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

