

Huang Liang 1.85 mm Female to 2.92 mm Female Adapter

SKU

ACC-HL-00017

MPN

ADU1-VF1-KF1

Description

The Huang Liang ADU1-VF1-KF1 Adapter is a 50 Ω coaxial RF adapter featuring a 1.85 mm female to 2.92 mm female interface. Designed for precision and versatility, the adapter supports frequencies from 0 GHz to 40 GHz and operates effectively within temperatures ranging from -40 °C to 105 °C.

Constructed from passivated stainless steel (303) and featuring gold-plated beryllium copper contacts, the adapter ensures durability and optimal signal integrity. Its free-hanging, straight body design facilitates seamless connections with compatible 1.85 mm, 2.4 mm, and 2.92 mm male interfaces.

Manufactured in Taiwan by Huang Liang, a company with over 30 years of expertise in RF technology, the adapter meets ISO 9001 quality standards and complies with RoHS regulations. This high-quality component is suitable for applications in military, telecommunications, and aerospace industries.



[Huang Liang](#)

Huang Liang is a Taiwanese manufacturer of precision coaxial connectors, adapters and cable assemblies. The company provide solutions to different industries including military, telecommunications, and aerospace.

Over 30 years of experience in developing and designing RF products, Huang Liang has overcome many challenges, resulting in unmatched expertise in the field of RF technology. Huang Liang ...

RF Connector Interface

RF Interface Body Shape Mounting

[1.85 mm Female](#) [Straight](#) [Free Hanging](#)

[2.92 mm Female](#) [Straight](#) [Free Hanging](#)

RF Specification

Start Frequency

0 GHz

Stop Frequency

40 GHz

RF Operating Voltage

≥ 250 Vrms

Input Impedance

50 Ω

Inner Contact Resistance

≤ 6 m Ω

Insulation Resistance

≥ 3000 m Ω

Outer Contact Resistance

≤ 2 m Ω

VSWR Measurement

Frequency VSWR Insertion Loss

40000 MHz $\leq 1.2:1$ 0.38 dB

Physical Specification

Body Material

[Stainless Steel \(303\)](#)

Body Plating

[Passivated](#)

Insulator Material

[PTFE / Teflon](#)

Weight

5.5 g

Compliance/Certifications

[ISO 9001 Quality Management](#)

,
[RoHS](#)

Contact Material

[Beryllium Copper](#)

Contact Plating

[Gold](#)

Min. Operating Temperature

-40 °C

Max. Operating Temperature


105 °C

Mating Cycles

> 500

Drawing

Image



Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

