

Page



Powertec Wireless Technology
ABN: 42 082 948 463
PO Box 1034, Ashmore City
Queensland, Australia, 4214
sales@powertec.com.au
1300 769 378

Huang Liang 1.85 mm Female to 2.92 mm Male Adapter

SKU
ACC-HL-00018
MPN
ADU1-VF1-KM1

Description

The Huang Liang ADU1-VF1-KM1 Adapter is a 50 Ω coaxial RF adapter designed for high-frequency applications, featuring a 1.85 mm Female to 2.92 mm Male connection. This adapter operates within a frequency range of 0 GHz to 40 GHz, ensuring optimal performance across various RF environments.

Constructed from Stainless Steel (303) with a Passivated finish, it offers durability and resistance to corrosion. The inner contacts, made from Beryllium Copper with Gold plating, guarantee excellent conductivity and reliability. It is suitable for extreme environments, with an operational temperature range of -65 °C to 150 °C.

The adapter's straight body design facilitates a free-hanging mounting mechanism, compatible with 1.85 mm Male, 2.4 mm Male, and 2.92 mm Female interfaces. Manufactured in compliance with ISO 9001 Quality Management and RoHS standards, it meets rigorous quality and environmental requirements.

Huang Liang, a Taiwanese leader in...

[Read More](#)



Huang Liang

Huang Liang is a Taiwanese manufacturer of precision coaxial connectors, adapters and cable assemblies. The company provide solutions to different industries including military, telecommunications, and aerospace.

Over 30 years of experience in developing and designing RF products, Huang Liang has overcome many challenges, resulting in unmatched expertise in the field of RF technology. Huang Liang ...

RF Connector Interface

RF Interface	Body Shape	Mounting
--------------	------------	----------

1.85 mm Female	Straight	Free Hanging
--------------------------------	--------------------------	------------------------------

2.92 mm Male	Straight	Free Hanging
------------------------------	--------------------------	------------------------------

RF Specification

Start Frequency

0 GHz

Stop Frequency

40 GHz

RF Operating Voltage

≥ 350 Vrms

Input Impedance

50 Ω

Inner Contact Resistance

≤ 3 m Ω

Insulation Resistance

$\geq 5000 \text{ m}\Omega$

Outer Contact Resistance

$\leq 2 \text{ m}\Omega$

VSWR Measurement

Frequency VSWR Insertion Loss

40000 MHz $\leq 1.2:1$ 0.25 dB

Physical Specification

Body Material

[Stainless Steel \(303\)](#)

Body Plating

[Passivated](#)

Insulator Material

[PTFE / Teflon](#)

Compliance/Certifications

[ISO 9001 Quality Management](#)

,

[RoHS](#)

Contact Material

[Beryllium Copper](#)

Contact Plating

[Gold](#)

Min. Operating Temperature

-65 °C

Max. Operating Temperature


150 °C

Mating Cycles

> 500

Drawing

Image



Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

